

Axis video encoders

	1-channel video encoders				4- and 6-channel video encoders				
	AXIS 241S 	AXIS 243SA 	AXIS 247S 	AXIS Q7401² 	AXIS 240Q 	AXIS 241Q 	AXIS 241QA 	AXIS 243Q 	AXIS Q7406 
Video compression	MPEG-4 , Motion JPEG	MPEG-4 , Motion JPEG	MPEG-4 , Motion JPEG	H.264, Motion JPEG	Motion JPEG	MPEG-4 , Motion JPEG	MPEG-4 , Motion JPEG	MPEG-4 , Motion JPEG	H.264, Motion JPEG
Max video resolution (pixels)	4CIF: 704x480 (NTSC) 704x576 (PAL)	4CIF: 704x480 (NTSC) 704x576 (PAL)	4CIF: 704x480 (NTSC) 704x576 (PAL)	D1: 720x480 (NTSC) 720x576 (PAL)	4CIF: 704x480 (NTSC) 704x576 (PAL)	4CIF: 704x480 (NTSC) 704x576 (PAL)	4CIF: 704x480 (NTSC) 704x576 (PAL)	4CIF: 704x480 (NTSC) 704x576 (PAL)	D1: 720x480 (NTSC) 720x576 (PAL)
Frames per second H.264 (NTSC/PAL) in maximum resolution				30/25 (D1)					30/25 (D1) per channel
Frames per second Motion JPEG (NTSC/PAL) in maximum resolution	30/25 (4CIF)	30/25 (4CIF)	30/25 (4CIF)	30/25 (D1)	6/5 (4CIF) per channel	30/25 (4CIF) using 1 channel, 30/25 (CIF) per channel using 4 channels	30/25 (4CIF) using 1 channel, 30/25 (CIF) per channel using 4 channels	30/25 (4CIF) per channel	30/25 (D1) per channel
Frames per second MPEG-4 (NTSC/PAL) in maximum resolution	21/17 (4CIF) 30/25 (2CIF)	30/25 (4CIF)	27/23 (4CIF) 30/25 (VGA)			21/17 (4CIF) using 1 channel, 20/17 (CIF) per channel using 4 channels	21/17 (4CIF) using 1 channel, 20/17 (CIF) per channel using 4 channels	30/25 (4CIF) per channel	
Video source	1 BNC composite or Y/C video input ¹	1 BNC composite or Y/C video input ¹	1 BNC composite input	1 BNC composite input	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs	6 BNC composite inputs
Audio support		Two-way	One-way	Two-way			Two-way		
Alarm in-/outputs	4/4	4/4	1/1	4 configurable inputs/outputs	4/4	4/4	4/4	4/4	2 configurable inputs/ outputs per channel
Intelligent video	Motion detection	Motion detection Audio detection Tampering alarm	Motion detection Audio detection	Motion detection Audio detection Tampering alarm	Motion detection	Motion detection	Motion detection	Motion detection, Tampering alarm	Motion detection Tampering alarm
Pan/tilt/zoom support	●	●		●	●	●	●	●	●
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4	IPv4/v6, QoS	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)			Class 2/3	Class 2/3					
Serial connectors	RS-232, RS-485	RS-232, RS-485		RS-422/RS-485	RS-232, RS-485	RS-232, RS-485	RS-232, RS-485	RS-485	RS-485
Standalone version	●	●	●	●	●	●	●		
Blade version	●				●	●		●	●

1) Y/C video requires converter cable 2) Supports local storage with SD/SDHC card

Rack solutions

Designed for high-density installations, Axis video encoder rack solutions accommodate multiple video encoder blades in the same rack.

	AXIS 291 1U Video Server Rack	AXIS Video Server Rack	AXIS Q7900 Rack
			
Number of slots	3	12	14
Blades supported	AXIS 240Q AXIS 241Q AXIS 241S AXIS 243Q AXIS Q7406	AXIS 240Q AXIS 241Q AXIS 241S	AXIS 240Q AXIS 241Q AXIS 241S AXIS 243Q AXIS Q7406
Maximum number of channels	18	48	84
Rack size	1U	3U	4U
Rack width	19"	19"	19"
Built-in power supply	●	●	●
Network	One Ethernet 10BASE-T/ 100BASE-TX/1000BASE-T (Gigabit Ethernet) port	One Ethernet 10BASE-T/ 100BASE-TX port	Four Ethernet 10BASE-T/ 100BASE-TX/1000BASE-T (Gigabit Ethernet) ports

For more information, visit www.axis.com/products/video/video_server/

Distributed by:

Accessories

AXIS 295 Video Surveillance Joystick

AXIS 295 Video Surveillance Joystick is a USB device specifically designed for responsive and accurate control of all Axis PTZ (pan/tilt/zoom) and PTZ dome network cameras. It features a three-axis, durable (Hall-effect) joystick and 12 programmable push-buttons. Easy to install, just connect the joystick to the USB port and control the Axis cameras.

Illuminators

Illuminators for indoor/outdoor surveillance in low light or complete darkness.

Power over Ethernet Midspans and Splitters

Axis Power over Ethernet midspan and splitters offer an easy, fast and cost-effective solution for powering network video products without the need to install power outlets and electrical cabling.

High PoE midspans and splitters are available for network cameras such as PTZ and PTZ dome cameras that require higher power consumption.

AXIS 292 Network Video Decoder

AXIS 292 Network Video Decoder decodes digital video and audio streams into analog video signals.

Video management software


AXIS Camera Station

Comprehensive, easy-to-use video management software for monitoring, recording, playback and event management. Specially designed for Axis network cameras and video encoders.

AXIS Camera Station One

Software solution for viewing and recording live video from a single Axis network camera. Available for free download.

For more information, visit www.axis.com/products/video/software/

AXIS Camera Management

Powerful and efficient installation and management tool for Axis network video products. Available for free download.

Axis' Application Development Partners

A wide variety of software solutions for video surveillance, remote monitoring or broadcasting are available from more than 500 Axis Application Development Partners.

Axis fixed dome network cameras

	AXIS 209FD	AXIS 209MFD	AXIS 209FD-R	AXIS 209MFD-R	AXIS 216FD	AXIS 216FD-V	AXIS P3301	AXIS P3301-V	AXIS 216MFD	AXIS 216MFD-V	AXIS 225FD
											
Image sensor	1/4" progressive scan CMOS	1/3" progressive scan CMOS 1.3 megapixel	1/4" progressive scan CMOS	1/3" progressive scan CMOS 1.3 megapixel	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" progressive scan CMOS 1.3 megapixel	1/3" progressive scan CMOS 1.3 megapixel	1/4" progressive scan CCD
Lens	3.0 mm/F2.0 fixed iris	3.6 mm/F1.8 fixed iris	3.0 mm/F2.0 fixed iris	3.6 mm/F1.8 fixed iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 5.8 mm/F1.4 DC-iris
Day and night											Automatic
Min illumination/light sensitivity (lux)	1.5 - 10,000	3 - 10,000	1.5 - 10,000	3 - 10,000	1	1	1	1	2	2	1 (color) 0.2 (B/W)
Video compression	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG
Max video resolution (pixels)	640 x 480	1280 x 1024	640 x 480	1280 x 1024	640 x 480	640 x 480	640 x 480	640 x 480	1280 x 1024	1280 x 1024	640 x 480
Frames per second	30 (640x480)	12 (1280x1024)	30 (640x480)	12 (1280x1024)	30 (640x480)	30 (640x480)	30 (640 x 480)	30 (640 x 480)	12 (1280x1024) 30 (800x600)	12 (1280x1024) 30 (800x600)	30 (640x480)
Audio support					Two-way, built-in mic	Two-way, built-in mic	Two-way, built-in mic	Two-way, built-in mic	Two-way, built-in mic	Two-way, built-in mic	
Alarm in-/outputs					1/1	1/1	1/1	1/1	1/1	1/1	2/1
Intelligent video	Motion detection	Motion detection	Motion detection Tampering alarm	Motion detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Tampering alarm
Security	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 2	Class 2	Class 1	Class 1	Class 2 (without heater)
Serial connectors											RS-485
Outdoor use											●
Other			IP66-rated, rugged, for mobile video surveillance	IP66-rated, rugged, for mobile video surveillance	Tamper-resistant	Vandal-resistant	WDR, Tamper-resistant	WDR, Vandal-resistant	Tamper-resistant	Vandal-resistant	Vandal-resistant, IP66-rated, heater and fan

Axis fixed network cameras

	AXIS 206	AXIS 207/ AXIS 207W	AXIS 207MW	AXIS M1011/ AXIS M1011-W	AXIS M1031-W	AXIS 210	AXIS 210A	AXIS 211	AXIS 211A	AXIS 211W
										
Image sensor	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" progressive scan CMOS 1.3 megapixel	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CCD	1/4" progressive scan CCD	1/4" progressive scan CCD	1/4" progressive scan CCD	1/4" progressive scan CMOS
Lens	4.0 mm/F2.0 fixed iris	4.0 mm/F2.0 fixed iris	3.6 mm/F1.8 fixed iris	4.4 mm/F2.0 fixed iris	4.4 mm/F2.0 fixed iris	4.0 mm/F1.2 fixed iris CS mount	4.0 mm/F1.2 fixed iris CS mount	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount
Day and night										
Min illumination/light sensitivity (lux)	4 - 10,000	1 - 10,000	2 - 10,000	1 - 10,000	1 - 10,000 0 with LED on	1 - 10,000	1 - 10,000	0.75	0.75	0.75
Video compression	Motion JPEG	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	H.264 Motion JPEG MPEG-4	H.264 Motion JPEG MPEG-4	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	1280 x 1024	640 x 480	640 x 480	640 x 480	640 x 480	640 x 480	640 x 480	640 x 480
Frames per second	30 (640x480)	30 (640x480)	12 (1280 x 1024)	30 (640x480)	30 (640x480)	30 (640x480)	30 (640x480)	30 (640x480)	30 (640x480)	30 (640x480)
Audio support		One-way, built-in mic	One-way, built-in mic		Two-way, built-in mic and speaker		Two-way, built-in mic		Two-way, built-in mic	Two-way, built-in mic
Alarm in-/outputs		1/1	1/1			1/1	1/1	1/1	1/1	1/1
Intelligent video		Motion detection Audio detection	Motion detection Audio detection	Motion detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection	Motion detection Audio detection Tampering alarm	Motion detection	Motion detection Audio detection Tampering alarm	Motion detection Audio detection
Security	Multi-level passwords	Multi-level passwords IP filtering ¹ HTTPS encryption ¹	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4	IPv4/v6 ¹ , QoS ¹	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)	PoE splitter available	PoE splitter available	PoE splitter available	PoE splitter available	PoE splitter available	PoE splitter available	Class 2	Class 2	Class 2	Class 2
Serial connectors										
Outdoor use								Requires housing	Requires housing	Requires housing
Other		Wireless IEEE 802.11b/g ¹	Wireless IEEE 802.11b/g	AXIS M1011-W: wireless IEEE 802.11b/g	Built-in PIR sensor Illumination LED Wireless IEEE 802.11b/g					Wireless IEEE 802.11b/g

1) AXIS 207W only

Axis pan/tilt/zoom network camera

	AXIS 211M	AXIS 221	AXIS 223M	AXIS Q1755
				
	1/3" progressive scan CMOS 1.3 megapixel	1/3" progressive scan CCD	1/2.7" progressive scan CCD 2 megapixel	1/3" progressive scan CMOS 2 megapixel
	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 4.0 - 8.0 mm/F1.4 DC-iris, C mount ²	5.1 - 51 mm/F1.8 auto iris and autofocus 10x optical zoom 12x digital zoom
		Automatic	Automatic	Automatic
	1	0.65 (color) 0.08 (B/W)	1.5 (color) 0.2 (B/W)	2 (color) 0.2 (B/W)
	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	H.264 Motion JPEG
	1280 x 1024	640 x 480	1600x900 1600x1200	HDTV 1080i 1920x1080 HDTV 720p 1280x720
	12 (1280x1024) 30 (800x600)	45 (640x480) 60 (480x360)	12 (1600x900) 9 (1600x1200)	30/25
	Two-way, built-in mic		Two-way	Two-way, built-in mic
	1/1	2/1	2/1	2 configurable inputs/outputs
	Motion detection Audio detection	Motion detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm Gatekeeper
ds	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
	Class 2	Class 2	Class 2	Class 3
		RS-232, RS-485	RS-232, RS-485	RS-422/RS-485
	Requires housing	Requires housing	Requires housing	Requires housing
				SD/SDHC memory card slot and analog video out

²) Camera can be used with C/CS lens

	PTZ network cameras				
	AXIS 212 PTZ	AXIS 212 PTZ-V	AXIS 213 PTZ	AXIS 214 PTZ	AXIS 215 PTZ
					
Image sensor	1/2" progressive scan CMOS 3 megapixel	1/2" progressive scan CMOS 3 megapixel	1/4" CCD	1/4" ExView HAD CCD	1/4" CCD
Lens	2.7 mm/F1.8 fixed iris 3x instant zoom	2.7 mm/F1.8 fixed iris 3x instant zoom	3.5 - 91 mm/F1.6 auto iris and autofocus 26x optical zoom 12x digital zoom	4.1 - 73.8 mm/F1.3 auto iris and autofocus 18x optical zoom 12x digital zoom	3.8 - 46 mm/F1.6 auto iris and autofocus 12x optical zoom 4x digital zoom
Day and night			Configurable Built-in IR lamp	Automatic	Automatic
Min illumination/ light sensitivity (lux)	10 lux wide mode 20 lux tele mode	10 lux wide mode 20 lux tele mode	1 (color) 0.1 (B/W)	0.3 (color) 0.005 (B/W)	1 (color) 0.3 (B/W)
Video compression	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	4CIF: 704x480 (NTSC), 704x576 (PAL)	4CIF: 704x480 (NTSC), 704x576 (PAL)	4CIF: 704x480 (NTSC), 704x576 (PAL)
Frames per second (NTSC/PAL)	30 (640x480) at max. zoom	30 (640x480) at max. zoom	30/25 (4CIF)	30/25 (4CIF)	30/25 (4CIF)
Pan/Tilt/Zoom	20 presets 140° pan 105° tilt Guard tour	20 presets 140° pan 105° tilt Guard tour	20 presets 340° pan 100° tilt	20 presets 340° pan 120° tilt	20 presets 360° pan via Auto-flip 180° tilt
Audio support	Two-way, built-in mic	Two-way	Two-way with AXIS 213CM	Two-way	Two-way
Alarm in-/outputs	1/1	1/1	2/3 with AXIS 213CM	1/1	1/1
Intelligent video	Motion detection Audio detection	Motion detection Audio detection	Motion detection	Motion detection Audio detection	Motion detection Audio detection
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4	IPv4/v6, QoS	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)	Class 1	Class 1			
Serial connectors			RS-232 with AXIS 213CM		
Outdoor use			Requires housing	Requires housing	Requires housing
Other	Continuous motion 24/7	Continuous motion 24/7 Vandal-resistant	Built-in IR light Analog video out with AXIS 213CM		Auto-flip and E-flip

k cameras

PTZ dome network cameras				
	AXIS 215 PTZ-E	AXIS 231D+	AXIS 232D+	AXIS 233D
				
	1/4" CCD	1/4" ExView HAD CCD	1/4" ExView HAD CCD	1/4" ExView progressive scan HAD CCD
	3.8 – 46 mm/F1.6 auto iris and autofocus 12x optical zoom 4x digital zoom	4.1 – 73.8 mm/F1.4 auto iris and autofocus 18x optical zoom 12x digital zoom	4.1 – 73.8 mm/F1.4 auto iris and autofocus 18x optical zoom 12x digital zoom	3.4 – 119 mm/F1.4 auto iris and autofocus 35x optical zoom 12x digital zoom
	Automatic		Automatic	Automatic
	1 (color) 0.3 (B/W)	0.3 (color)	0.3 (color) 0.005 (B/W)	0.5 (color) 0.008 (B/W)
	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG
	4CIF: 704x480 (NTSC), 704x576 (PAL)	4CIF: 704x480 (NTSC), 704x576 (PAL)	4CIF: 704x480 (NTSC), 704x576 (PAL)	4CIF: 704x480 (NTSC), 704x576 (PAL)
	30/25 (4CIF)	30/25 (4CIF)	30/25 (4CIF)	30/25 (4CIF)
	20 presets 360° pan via Auto-flip 180° tilt	50 presets 360° endless pan 90° tilt Guard tour	50 presets 360° endless pan 90° tilt Guard tour	100 presets 360° endless pan 180° tilt Guard tour
				Two-way
		4/4	4/4	4/4
	Motion detection	Motion detection	Motion detection	Motion detection Audio detection
	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
	●	Requires housing	Requires housing	Requires housing
	Auto-flip and E-flip	Continuous motion 24/7, WDR	Continuous motion 24/7, WDR	Continuous motion 24/7, E-flip, Image stabilizer, WDR, Auto-tracking

Axis network camera housings

Axis network camera housings, worldwide

Product	Compatible with:	Product	Compatible with:
 AXIS 206/207 Vandal-Resistant Housing Aluminum construction Indoor	AXIS 206, AXIS 207	 AXIS T95A Series Dome Housing Aluminum construction Indoor/outdoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+, AXIS 233D

Axis network camera housings, Europe

Product	Compatible with:	Product	Compatible with:
 VT Vandal-Resistant Housing AVTPSC Steel construction Indoor	AXIS 210 (indoors only), AXIS 210A (indoors only), AXIS 211, AXIS 211A, AXIS 211M, AXIS 211W, AXIS 221, AXIS 223M, AXIS Q1755	 VT Verso Housing VT Verso Cool Outdoor Housing Technopolymer plastic Indoor/outdoor	AXIS 210 (indoors only), AXIS 210A (indoors only), AXIS 211, AXIS 211A, AXIS 211M, AXIS 211W, AXIS 221, AXIS 223M, AXIS Q1755
 AXIS Hov Housing VT Aluminum construction Indoor/outdoor	AXIS 210 (indoors only), AXIS 210A (indoors only), AXIS 211, AXIS 211A, AXIS 211M, AXIS 211W, AXIS 221, AXIS 223M, AXIS Q1755	 VT DBH24K Dome Housing Technopolymer plastic Indoor/outdoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+

Axis network camera housings, North and Central America

Product	Compatible with:	Product	Compatible with:
 Indoor Vandal Resistant Housings Steel construction Indoor	AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 211W, AXIS 221, AXIS 223M, AXIS Q1755	 AXIS Fixed Wireless Housing Aluminum construction Outdoor	AXIS 211W
 AXIS Indoor Fixed Housing Aluminum construction Indoor	AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 211W, AXIS 221, AXIS 223M, AXIS Q1755	 AXIS Pendant Dome Indoor Plastic construction Indoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+,AXIS 232D+, AXIS 233D
 AXIS Indoor Fixed Camera Dome Steel construction Indoor	AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 211W, AXIS 221, AXIS 223M, AXIS Q1755	 AXIS Indoor Recessed Enclosure Steel construction Indoor	AXIS 213 PTZ
 AXIS 206/207 Ceiling-Mount Housing Steel construction Indoor	AXIS 206, AXIS 207	 AXIS Pendant Dome Outdoor Plastic construction Indoor/outdoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+, AXIS 233D
 AXIS Outdoor Fixed Housing Aluminum construction Outdoor	AXIS 211, AXIS 211A, AXIS 211W, AXIS 221, AXIS 223M, AXIS Q1755	 AXIS Pendant Vandal Dome Aluminum construction Indoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+

For more information, visit www.axis.com/accessories