



— DSA-3100

Wireless Service Gateway

The DSA-3100 Wireless Service Gateway is a Network Access Control System (NACS) that manages intelligent AAA (authentication, authorization and accounting) for all wire and wireless network users. This security device coordinates ISO Layer 2, 3, 4 operations to provide your network with comprehensive functions, including IP plug and play, station isolation, traffic management and accounting, and network policy enforcement.

Network Access Security

The DSA-3100 Wireless Service Gateway provides you a comfortable and secure way to provide entrusted computers access to your LAN/WAN. The system guarantees that only registered users are able to use network resources.

AAA Function Execution

The DSA-3100 performs for you authentication, authorization and accounting (AAA), three basic issues that are encountered frequently in many network services. Examples of these services are dial in access to Internet, electronic commerce, Internet printing, and Mobile IP. Authentication acts to verify an identity so authorization can be granted to access a resource. Accounting collects resource consumption data for the purposes of trend analysis, and capacity planning, billing, auditing, and cost allocation.

Can Be Used on Commercial Network

The DSA-3100 can also be installed in a commercial network providing services to public. Authentication is needed to make sure that the user of the service is who he claims to be. This is quite important, because you don't want that someone else is using the service you have paid for. After the user has been authenticated we need a way to ensure that the user is authorized to do the things he is requesting. For example, if you are a normal user you don't have the permissions to access all the files in a file system. Usually authorization is provided by using access control lists or policies. Accounting collects information of the network usage for billing, capacity planning and other purposes.

Key Features

- 3 10/100Mbps Fast Ethernet ports for WAN connection, trusted LAN connection and untrusted LAN connection
- Manages up to 250 user account data with internal user account database
- Supports up to 50 on-line users
- ID/Password based authentication and authorization
- POP3, RADIUS and LDAP external authentication mechanism
- On-line status monitoring and history traffic data review
- SSL protected access to the administration interface and user authentication interface
- Customizable user login, logout web interface
- Customizable user logout timer
- Customizable target URL
- Built-in DHCP server
- High-speed policy routing engine
- Customizable peremptory traffic redirection
- NTP client

DSA-3100

Technical Specifications

Functions Provided

Manages up to 250 user account data with internal user account database

Supports up to 50 on-line users

ID/Password based authentication and authorization

- Can be combined with MAC address locking to provide stricter access control

POP3, RADIUS and LDAP external authentication mechanism support

- Only one of these can be selected at a time

On-line status monitoring and history traffic data review

SSL protected access to the administration interface and user authentication interface

Customizable user login & logout web interface

Customizable user logout timer

Customizable target URL for users who successfully get authorization

Console mode administration interface via serial console port

NAT support for managed clients

Static IP, DHCP client and PPPoE client on WAN interface

Built-in DHCP server to service managed clients

Built-in high-speed policy routing engine

Customizable preemptory traffic redirection (IP and Port Redirect)

Built-in NTP client

Local network port for connecting a trusted network

- Permits access to WAN, and LAN from local network without authentication
- Permits connection to wired Ethernet while connecting the wireless network to this Ethernet port

Hardware

CPU

NS GX-1 300 MHz

Memory

SDRAM 32 MB

Device Ports

- WAN port: 10/100Mbps Fast Ethernet
- LAN port: 10/100Mbps Fast Ethernet connects to workstations & servers that do not need authentication
- LAN port: 10/100Mbps Fast Ethernet connects to workstations & devices that need authentication
- Console port: RS-232 (default set to 115200, n, 8, 1, no flow control)

Physical & Environmental

Power Supply

External power adapter

Power Input

DC 5V/3A

Dimensions

45 mm (H) x 163 mm (D) x 215 mm (W)

Operating Temperature

0° - 50°C

Wireless Service Gateway

Storage Temperature

-25° - 55° C

EMI Certification

- FCC Class A
- CE Class A
- VCCI Class A
- C-Tick

Safety

- UL
- CSA
- TUV/GS
- T-Mark



ACN 052 202 838

Ordering Information

DSA-3100

Wireless Service Gateway

Please specify your order as follows:

DSA-3100/A	with US standard power adapter
DSA-3100/B	with UK standard power adapter
DSA-3100/E	with EU standard power adapter
DSA-3100/CN	with China standard power adapter (China packaging)
DSA-3100/N	with Australia standard power adapter
DSA-3100/U	no power adapter

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-949-788-0805	FAX: 1-949-753-7033
Canada	TEL: 1-905-8295033	FAX: 1-905-8295095
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Benelux	TEL: 31-10-2045740	FAX: 31-10-2045880
Italy	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Norway	TEL: 47-22-309075	FAX: 47-22-309085
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914
Middle East	TEL: 9714-8834234	FAX: 9714-8834394
Turkey	TEL: 90-212-335-2553	FAX: 90-212-335-2500
Chile	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
South Africa	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 01 (Mar. 2003)
Printed in Taiwan