



### Overview

#### HP Z230 SFF Workstation



1. External 5.25" bay
2. External/internal shared 3.5" bay
3. Power button
4. Front I/O (top to bottom order): 2 USB 2.0 ports, 2 USB 3.0 ports, Microphone/Headphone, Headphone
5. Optional SFF tower stand

Overview



- 1. 1 Audio Line In, 1 Audio Line Out
- 2. 2 USB 3.0, 2 USB 2.0
- 3. 1 serial port
- 4. 3 DisplayPort (DP 1.2) outputs from Intel HD graphics (available on specific processors only)
- 5. RJ-45 to integrated GBE
- 6. 2 USB 2.0
- 7. PS/2 ports (keyboard, mouse)

Form Factor	Small Form Factor
Operating Systems	<div>Preinstalled:<ul style="list-style-type: none"><li>Windows 7 Ultimate 64-bit</li><li>Windows 7 Professional 32/64</li><li>Windows 8.1 Pro 64-bit</li><li>Windows 8.1 Simplified Chinese Edition 64-bit</li><li>Windows 8.1 Pro Downgrade to Windows 7 Professional 32-bit</li><li>Windows 8.1 Pro Downgrade to Windows 7 Professional 64-bit</li><li>Windows 8.1 Pro Downgrade to Windows 7 Professional 32-bit (National Academic)</li><li>Windows 8.1 Pro Downgrade to Windows 7 Professional 64-bit (National Academic)</li><li>HP Installer Kit for Linux [includes drivers for 64-bit OS versions of Red Hat Enterprise Linux 6 and SUSE Linux Enterprise Desktop (SLED) 11]</li><li>SUSE Linux Enterprise Desktop 11 64-bit (90 day license)</li></ul></div>

Overview

	<ul style="list-style-type: none"><li>Red Hat Enterprise Linux Workstation (1 year paper license available; Preinstall not available)</li></ul> <p>Supported:</p> <ul style="list-style-type: none"><li>Genuine Windows® 7 Enterprise 32/64</li></ul> <p>Notes: For detailed OS/hardware support information for Linux, see: <a href="http://www.hp.com/support/linux_hardware_matrix">http://www.hp.com/support/linux_hardware_matrix</a></p>
--	--

Overview

Name	Cores	Clock Speed (GHz)	Intel® Turbo Boost Technology <sup>1</sup>	Cache (MB)	Memory Speed (MHz)	Hyper-Threading	Integrated Graphics	Featuring Intel® vPro™ Technology	TDP (W)
Intel® Xeon® processor E3-1281v3	4	3.7	4.1	8	1600	Y	N/A	Y	80W
Intel® Xeon® processor E3-1280v3	4	3.6	4.0	8	1600	Y	N/A	Y	80W
Intel® Xeon® processor E3-1271v3	4	3.6	4.0	8	1600	Y	N/A	Y	80W
Intel® Xeon® processor E3-1270v3	4	3.5	3.9	8	1600	Y	N/A	Y	80W
Intel® Xeon® processor E3-1246v3	4	3.5	3.9	8	1600	Y	Intel HD Graphics P4600	Y	84W
Intel® Xeon® processor E3-1245v3	4	3.4	3.8	8	1600	Y	Intel HD Graphics P4600	Y	84W
Intel® Xeon® processor E3-1241v3	4	3.5	3.9	8	1600	Y	N/A	Y	80W
Intel® Xeon® processor E3-1240v3	4	3.4	3.8	8	1600	Y	N/A	Y	80W
Intel® Xeon® processor E3-1231v3	4	3.4	3.8	8	1600	Y	N/A	Y	80W
Intel® Xeon® processor E3-1230v3	4	3.3	3.7	8	1600	Y	N/A	Y	80W
Intel® Xeon® processor E3-1226v3	4	3.3	3.7	8	1600	N	Intel HD Graphics P4600	Y	84W
Intel® Xeon® processor E3-1225v3	4	3.2	3.6	8	1600	N	Intel HD Graphics P4600	Y	84W
Intel® Core™ i7-4790 processor	4	3.6	4.0	8	1600	Y	Intel HD Graphics 4600	Y	84W
Intel® Core™ i7-4771 processor	4	3.5	3.9	8	1600	Y	Intel HD Graphics 4600	Y	84W
Intel® Core™ i7-4770 processor	4	3.4	3.9	8	1600	Y	Intel HD Graphics 4600	Y	84W
Intel® Core™ i5-4690 processor	4	3.5	3.9	6	1600	N	Intel HD Graphics 4600	Y	84W
Intel® Core™ i5-4670 processor	4	3.4	3.8	6	1600	N	Intel HD Graphics 4600	Y	84W
Intel® Core™ i5-4590 processor	4	3.3	3.7	6	1600	N	Intel HD Graphics 4600	Y	84W
Intel® Core™ i5-4570 processor	4	3.2	3.6	6	1600	N	Intel HD Graphics 4600	Y	84W
Intel® Core™ i3-4350 processor	2	3.6	N/A	4	1600	Y	Intel HD Graphics 4600	N	54W

### Overview

<b>Available Processor Disclaimers</b>	<p>Integrated Intel® HD graphics is not supported on the Intel® Xeon Processor E3-1230v3, E3-1240v3, E3-1270v3 or E3-1280v3.</p> <p>Intel® Xeon E3, Intel Core i3 and Intel Pentium processors can support either ECC or non-ECC memory; Intel® Core i5/i7 processors only support non-ECC memory.</p> <p>Intel's numbering is not a measurement of higher performance. Processor numbers differentiate features within each processor family, not across different processor families. See: <a href="http://www.intel.com/products/processor_number/">http://www.intel.com/products/processor_number/</a> for details.</p> <p>64-bit computing on Intel® 64 architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel 64 architecture. Processor will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. See: <a href="http://www.intel.com/info/em64t">http://www.intel.com/info/em64t</a> for more information.</p> <p>Dual-Core and Quad-Core technologies are designed to improve performance of multithreaded software products and hardware-aware multitasking operating systems and may require appropriate operating system software for full benefits; check with software provider to determine suitability; Not all customers or software applications will necessarily benefit from use of these technologies.</p>
<b>Color</b>	Jack Black
<b>Convertibility</b>	The Z230 SFF can either be placed flat on the desktop or made to stand on the desk with the optional tower stand.
<b>Expansion Slots (see system board section for more details)</b>	<ul style="list-style-type: none"> <li>• 1 PCIe Gen3 x16 slot</li> <li>• 1 PCIe Gen2 x4 slot /x16 connector</li> <li>• 1 PCIe Gen2 x1 slot/x4 connector</li> <li>• 1 PCIe Gen2 x1 slot</li> </ul> <p>(all slots are Low Profile)</p> <p><b>Note:</b> In the PCIe Gen3 x16 slot, if it is not being used for a graphics card, only cards certified as After Market Options for this platform are supported.</p>
<b>Expansion Bays (see storage section for more details)</b>	<ul style="list-style-type: none"> <li>• 1 external Half Height 5.25" bay</li> <li>• 1 shared internal/external 3.5" bay</li> <li>• 1 internal 3.5" bay</li> <li>• 1 internal 2.5" bay (for SSD only)</li> </ul>
<b>Front I/O</b>	2 USB 3.0, 2 USB 2.0, 1 Headphone, and 1 Microphone
<b>Internal I/O</b>	1 USB 3.0 and 3 USB 2.0 ports available as 2 separate 2x10(3.0 x1, 2.0 x1) and 2x5(2.0 x2) header: supports one HP Internal USB 2.0 Port Kit and one USB 3.0 Media Card Reader.
<b>Rear I/O</b>	3 DisplayPort (DP 1.2) outputs from Intel HD graphics (available on specific processors only); 2 USB 3.0 ports, 4 USB 2.0 ports, 2 serial ports (1 standard, 1 optional), 1 parallel port (optional), 2 PS/2, RJ-45 (LoM), 1 Audio Line-in, and 1 Audio Line-out; 2 IEEE 1394b ports (optional).
<b>Interfaces Supported</b>	14-in-1 Media Card Reader (optional)
<b>Chassis Dimensions (H x W x D)</b>	Standard desktop orientation: 100 x 337 x 384 mm (3.95 x 13.3 x 15.1 in); Optional SFF Tower orientation (excluding stand dimension): 337 x 100 x 384 mm (13.3 x 3.95 x 15.1 in)
<b>Weight</b>	Exact weights depend upon configuration;

### Overview

	<p>Typical Weight* 7.2 kg (15.87 lbs)  Shipping Weight* 9.8 kg (21.6 lbs)  Max Supported Weight (desktop orientation) 35 kg (77 lb)</p> <p>Note*: Configured with 2 3.5" hard drives, 1 optical drive, 2 DIMMs and 1 NVIDIA Quadro K600 graphics card</p>
<b>Temperature</b>	<p>Operating: 5° to 35°C (40° to 95°F)  Non-operating: -40° to 60°C ( -40° to 140°F)</p> <p>Notes: Derate the maximum operating temperature by one degree C (1.8 degrees F) for every 305m (1,000 ft) altitude over 1,524m (5,000 ft).</p>
<b>Humidity</b>	<p>Operating: 8% to 85%  Non-operating: 8% to 90%</p>
<b>Maximum Altitude (non-pressurized)</b>	<p>Operating: 3,000 m; 10,000 ft  Non-operating: 9,100 m; 30,000 ft</p>
<b>Power Supply</b>	<p>240W 92% Efficiency wide-ranging, active Power Factor Correction (PFC)</p> <p>240W Standard Efficiency wide-ranging, active PFC Power Supply option available in some countries. The Power Supply Efficiency Report for the 240W, 92% efficiency power supply may be found at these links:</p> <p><a href="http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD%20COMPANY_PS-4241-1HA_240W_ECOS%203449_Report.pdf">http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD%20COMPANY_PS-4241-1HA_240W_ECOS%203449_Report.pdf</a></p> <p><a href="http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD_D12-240P2A_240W_ECOS%203384_Report.pdf">http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD_D12-240P2A_240W_ECOS%203384_Report.pdf</a></p> <p><a href="http://www.plugloadsolutions.com/psu_reports/Hewlett-Packard%20Company_DPS-240AB-3%20A_240W_ECOS%203416_Report.pdf">http://www.plugloadsolutions.com/psu_reports/Hewlett-Packard%20Company_DPS-240AB-3%20A_240W_ECOS%203416_Report.pdf</a></p> <p><a href="http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD%20COMPANY_PCC002-020H2_240W_ECOS%203440_Report.pdf">http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD%20COMPANY_PCC002-020H2_240W_ECOS%203440_Report.pdf</a></p>
<b>Backup Devices</b>	<p>For a complete listing of compatible DAT tape drives, LTO tape drives and RDX Removable Disk Backup System offerings, please visit <a href="http://www.hp.com/go/connect">http://www.hp.com/go/connect</a></p>
<b>Chipset</b>	<p>Intel® C226 chipset</p>
<b>Memory</b>	<p>4 DIMM slots, supporting up to 32GB ECC/non-ECC, DDR3 1600 MHz</p>
<b>Memory disclaimers</b>	<p>The CPUs determine the speed at which the memory is clocked. If a 1333 MHz capable CPU is used in the system, the maximum speed the memory will run at is 1333 MHz regardless of the specified speed of the memory.</p>
<b>Workstation ISV Certifications</b>	<p>See the latest list of certifications at <a href="http://www.hp.com/united-states/campaigns/workstations/partnerships.html">http://www.hp.com/united-states/campaigns/workstations/partnerships.html</a></p>

### Supported Components

#### Processors

	Factory Configured	Option Kit	Support Notes
<b>Intel® Xeon® processor E3-1200 v3 family (Z230)</b>			
Intel® Xeon® processor E3-1281v3, Quad-Core, 8 MB cache, 3.7 GHz, up to 4.1 GHz with Intel Turbo Boost Technology	Y	N	See Note 2
Intel® Xeon® processor E3-1280v3, Quad-Core, 8 MB cache, 3.6 GHz, up to 4.0 GHz with Intel Turbo Boost Technology	Y	N	See Note 2
Intel® Xeon® processor E3-1271v3, Quad-Core, 8 MB cache, 3.6 GHz, up to 4.0GHz with Intel Turbo Boost Technology	Y	N	See Note 2
Intel® Xeon® processor E3-1270v3, Quad-Core, 8 MB cache, 3.5 GHz, up to 3.9 GHz with Intel Turbo Boost Technology	Y	N	See Note 2
Intel® Xeon® processor E3-1246v3, Quad-Core, 8 MB cache, 3.5 GHz, up to 3.9 GHz with Intel Turbo Boost Technology	Y	N	See Note 2
Intel® Xeon® processor E3-1245v3, Quad-Core, 8 MB cache, 3.4 GHz, up to 3.8 GHz with Intel Turbo Boost Technology	Y	N	See Note 2
Intel® Xeon® processor E3-1241v3, Quad-Core, 8 MB cache, 3.5 GHz, up to 3.9 GHz with Intel Turbo Boost Technology	Y	N	See Note 2
Intel® Xeon® processor E3-1240v3, Quad-Core, 8 MB cache, 3.4 GHz, up to 3.8 GHz with Intel Turbo Boost Technology	Y	N	See Note 2
Intel® Xeon® processor E3-1231v3, Quad-Core, 8 MB cache, 3.4 GHz, up to 3.8 GHz with Intel Turbo Boost Technology	Y	N	See Note 2
Intel® Xeon® processor E3-1230v3, Quad-Core, 8 MB cache, 3.3 GHz, up to 3.7 GHz with Intel Turbo Boost Technology	Y	N	See Note 2
Intel® Xeon® processor E3-1226v3, Quad-Core, 8 MB cache, 3.3 GHz, up to 3.7 GHz with Intel Turbo Boost Technology	Y	N	See Note 2
Intel® Xeon® processor E3-1225v3, Quad-Core, 8 MB cache, 3.2 GHz, up to 3.6 GHz with Intel Turbo Boost Technology	Y	N	See Note 2
<b>4th generation Intel® Core™ processor family</b>			
Intel® Core™ i7-4790 processor, Quad-Core, 8 MB cache, 3.6 GHz, up to 4.0 GHz with Intel Turbo Boost Technology	Y	N	See Note 3
Intel® Core™ i7-4771 processor, Quad-Core, 8 MB cache, 3.5 GHz, up to 3.9 GHz with Intel Turbo Boost Technology	Y	N	See Note 3

### Supported Components

Intel® Core™ i7-4770 processor, Quad-Core, 8 MB cache, 3.4 GHz, up to 3.9 GHz with Intel Turbo Boost Technology	Y	N	See Note 3
Intel® Core™ i5-4690 processor, Quad-Core, 6 MB cache, 3.5 GHz, up to 3.9 GHz with Intel Turbo Boost Technology	Y	N	See Note 3
Intel® Core™ i5-4670 processor, Quad-Core, 6 MB cache, 3.4 GHz, up to 3.8 GHz with Intel Turbo Boost Technology	Y	N	See Note 3
Intel® Core™ i5-4590 processor, Quad-Core, 6 MB cache, 3.3 GHz, up to 3.7 GHz with Intel Turbo Boost Technology	Y	N	See Note 3
Intel® Core™ i5-4570 processor, Quad-Core, 6 MB cache, 3.2 GHz, up to 3.6 GHz with Intel Turbo Boost Technology	Y	N	See Note 3
Intel® Core™ i3-4350 processor, Dual-Core, 4 MB cache, 3.6 GHz	Y	N	See Note 2
Intel® Core™ i3-4330 processor, Dual-Core, 4 MB cache, 3.5 GHz	Y	N	See Note 2
Intel® Core™ i3-4130 processor, Dual-Core, 4 MB cache, 3.4 GHz	Y	N	See Note 2
<b>Dual Core Intel® Pentium® Processors (Z230)</b>			
Intel® Pentium® G3220 processor, Dual-Core, 3 MB cache, 3.0 GHz	Y	N	See Note 2
Intel® Pentium® G3240 processor, Dual-Core, 3 MB cache, 3.1 GHz	Y	N	See Note 2

**NOTE 1:** Intel HD Graphics P4600 supports workstation-specific graphics drivers for improved compatibility and performance on select professional applications, compared to Intel HD Graphics 4600.

**NOTE 2:** These processors support either ECC or non-ECC memory

**NOTE 3:** These processors support only non-ECC memory

### Monitors / Displays

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP DreamColor LP2480zx Professional Display				
HP Z Display Z30i 30-inch IPS LED Backlit Monitor				
HP Z Display Z27i 27-inch IPS LED Backlit Monitor				
HP Z Display Z24i 24-inch IPS LED Backlit Monitor				
HP Z Display Z23i 23-inch IPS LED Backlit Monitor				
HP Z Display Z22i 21.5-inch IPS LED Backlit Monitor				
HP ZR2740w 27-inch LED Backlit IPS Monitor				
HP ZR2440w 24-inch LED Backlit IPS Monitor				
HP ZR2330w 23-inch IPS LED Backlit Monitor				
Supported by all Operating Systems available from HP				
Screen Size Diagonally Measured				

### Hard Drives

#### SATA Hard Drives

Factory	Option	Option Kit	Support
---------	--------	------------	---------



### Supported Components

		Configured	Kit	Part Number	Notes
<b>SATA (Serial ATA) Hard Drives for HP Workstations</b>					
500GB SATA 7200 rpm 6Gb/s 3.5" HDD		Y	Y	LQ036AA	
1TB SATA 7200 rpm 6Gb/s 3.5" HDD		Y	Y	LQ037AA	
2.0TB SATA 7200 rpm 6Gb/s 3.5" HDD		Y	Y	QB576AA	
3.0TB SATA 7200 rpm 6Gb/s 3.5" HDD		Y	Y	QF298AA	
250GB SATA 10K rpm SFF HDD		Y	Y	B8X18AA	
500GB SATA 10K rpm SFF HDD		Y	Y	B8X19AA	
1TB SATA 10K rpm SFF HDD		Y	Y	B8X20AA	
500GB SATA 7.2K SED SFF HDD		Y	N	(not available today as After Market Option)	
<b>Sub-Section Description/Notes</b>	Note: The 2.5" internal drive bay on the Z230 SFF only supports a Solid State Drive, and not a 10K rpm HDD.				
<b>SATA Solid State Drives</b>	<b>HP Solid State Drives (SSDs) for Workstations</b>				
	HP 128GB SATA 6Gb/s SSD	Y	Y	A3D25AA	
	HP 256GB SATA 6Gb/s SSD	Y	Y	A3D26AA	
	HP 256GB SATA 6Gb/s SED SSD	Y	Y	(not available as After Market Option)	
	HP 512GB SATA 6Gb/s SSD	Y	Y	D8F30AA	
	HP 1TB SATA 6Gb/s SSD	Y	Y	F3C96AA	
	Intel Pro 1500 180GB SATA SSD	Y	Y	F5Z70AA	
	Samsung Enterprise 240GB SATA SSD	Y	Y	F0W94AA	
	Samsung Enterprise 480GB SATA SSD	Y	Y	TBD	
<b>Intelligent Disk Caching</b>	<b>Intelligent Disk Caching</b>				
	64GB SSD Disk Cache Module	Y	N	(not available today as After Market Option)	
<b>PCIe SSDs</b>	<b>PCIe SSDs for HP Workstations</b>				

### Supported Components

HP Z Turbo Drive 512GB SSD*	Y	Y	G3G89AA
HP Z Turbo Drive 256GB SSD*	Y	Y	G3G88AA

\* Each drive requires a PCIe x4 (minimum) slot to be available. Full performance is obtained only when using PCIe slots connected to the CPU. Non-CPU PCIe slots may see a decrease of up to 10%. Please see slot configuration recommendations at [www.hp.com/go/zturbo](http://www.hp.com/go/zturbo). Note that graphics cards, Thunderbolt™, and other devices will require PCIe slots.

### Hard Drive Controllers

	Factory Configured	Option Kit	Support Notes
<b>Integrated SATA Controller (Z230)</b>			
Integrated SATA Controller, RAID 0,1 supported: 5x 6 Gb/s ports	Y	N	
<b>Factory integrated RAID on motherboard for SATA drives</b>			
RAID 0 Configuration – Striped Array	Y	N	
RAID 1 Configuration – Mirrored Array	Y	N	
<b>NOTE 1:</b> Windows OS only; Supported only with two drives of identical type and capacity.			

SATA hardware RAID is not supported on Linux systems. The Linux kernel, with built-in software RAID, provides excellent functionality and performance. It is a good alternative to hardware-based RAID. Please visit <http://h20000.www2.hp.com/bc/docs/support/SupportManual/c00060684/c00060684.pdf> for RAID capabilities with Linux.

### Graphics

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes	Supported # of cards	Mixed
<b>Integrated Intel HD Graphics Media Accelerators (Z230)</b>						
Intel HD Graphics P4600	Y	N		Available on Intel® Xeon® E3-12x5 v3 processors only. See Note 1.	1	NO
Intel HD Graphics 4600	Y	N		Available on Intel Core™ i7-4xxx/ Core i5-4xxx/ Core i3-4330 processors. See Note 1. Available on Intel Core™ i7-4xxx/ Core i5-4xxx/ Core i3-	1	NO

### Supported Components

			4330 processors. See Note 1.		
Intel HD Graphics 4400	Y	N	Available on Intel Core i3-4130 processor. See Note 1.	1	NO
Intel HD Graphics	Y	N	Available on Intel Pentium® 3220 processor. See Note 1	1	NO

#### Professional 2D

NVIDIA NVS 310 512MB Graphics	Y	Y	A7U59AA	Can be mixed with one NVS 510	2	YES
NVIDIA NVS 315 1GB Graphics	Y	Y	E1U66AA		2	NO
NVIDIA NVS 510 2GB Graphics	Y	Y	C2J98AA	Can be mixed with one NVS 310	1	YES

#### Graphics Cable Adapters

HP DisplayPort To DVI-D Adapter	Y	Y	FH973AA		1	
HP DisplayPort To DVI-D Adapter (2-Pack)	Y	N			1	
HP DisplayPort To DVI-D Adapter (4-Pack)	Y	N			1	
HP DisplayPort To VGA Adapter	Y	Y	AS615AA		1	
HP DisplayPort to Dual Link DVI Adapter	Y	Y	NR078AA		1	

#### Entry 3D

AMD FirePro V3900 1GB Graphics	Y	Y	A6R69AA		1	NO
NVIDIA Quadro 410 512MB Graphics	Y	Y	A7U60AA		1	NO
NVIDIA Quadro K600 1GB Graphics	Y	Y	C2J92AA		1	NO

**Note 1:** Intermixing integrated Intel HD graphics and discrete graphics cards in order to drive more than three displays can be enabled using the Computer (F10) Setup Utility. However, HP recommends using only discrete graphics when four or more displays are required to be supported. Utility. However, HP

### Supported Components

recommends using only discrete graphics cards when four or more displays are required to be supported.

#### Memory

##### Sub-Section Description/Notes

Intel® Xeon E3, Intel Core i3 and Intel Pentium processors can support either ECC or non-ECC memory; Intel® Core i5/i7 processors only support non-ECC memory.

##### CTO

##### Support Notes

##### DDR3-1600 nECC Unbuffered DIMMs CTO

HP 32GB (4x8GB) DDR3-1600 nECC RAM

HP 16GB (2x8GB) DDR3-1600 nECC RAM

HP 16GB (4x4GB) DDR3-1600 nECC RAM

HP 8GB (2x4GB) DDR3-1600 nECC RAM

HP 4GB (1x4GB) DDR3-1600 nECC RAM

##### DDR3-1600 ECC Unbuffered DIMMs - CTO

HP 32GB (4x8GB) DDR3-1600 ECC RAM

HP 16GB (2x8GB) DDR3-1600 ECC RAM

HP 16GB (4x4GB) DDR3-1600 ECC RAM

HP 8GB (2x4GB) DDR3-1600 ECC RAM

HP 8GB (1x8GB) DDR3-1600 ECC RAM

HP 4GB (2x2GB) DDR3-1600 ECC RAM

HP 4GB (1x4GB) DDR3-1600 ECC RAM

##### Sub-Section Description/Notes

Two channels of DDR3 memory are supported. To realize full performance at least one DIMM must be inserted into each channel.

The CPUs determine the speed at which the memory is clocked. If a 1333 MHz capable CPU is used in the system, the maximum speed the memory will run at is 1333 MHz regardless of the specified speed of the memory.

##### AMO

##### Option Kit Part Number

##### Support Notes

##### DDR3-1600 nECC Unbuffered DIMMs AMO

HP 8GB (1x8GB) DDR3-1600 non-ECC RAM

B1S54AA

HP 4GB (1x4GB) DDR3-1600 nECC RAM

B1S53AA

##### DDR3-1600 ECC Unbuffered DIMMs - AMO

HP 8GB (1x8GB) DDR3-1600 ECC RAM

A2Z50AA

HP 4GB (1x4GB) DDR3-1600 ECC RAM

A2Z48AA

**NOTE:** Only unbuffered DDR3 DIMMs are supported.

#### Multimedia and Audio Devices

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Thin USB Powered Speakers, Low Halogen	Y	Y	KK912AA	
Integrated Realtek HD ALC221 Audio	Y	N		

### Supported Components

#### Optical and Removable Storage

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP 16X DVD-ROM SATA Drive (non Lightscribe)	Y	Y	AR629AA	
HP 16X DVD+/-RW SuperMulti SATA Drive	Y	Y	QS208AA	
HP Blu-ray Writer	Y	Y	AR482AA	
HP 14-in-1 Media Card Reader	Y	Y	E5G19AA	

Actual speeds may vary. Does not permit copying of commercially available DVD movies or other copyright protected materials. Intended for creation and storage of your original material and other lawful uses. Double Layer discs can store more data than single layer discs. However, double-layer discs burned with this drive may not be compatible with many existing single-layer DVD drives and players.

As Blu-ray is a new format containing new technologies, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD-DVD movies cannot be played on this workstation.

#### Controller Cards

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP IEEE 1394b FireWire PCIe Card	Y	Y	NK653AA	See Note 1
HP Thunderbolt-2 PCIe 1-port I/O Card	Y	Y	F3F43AA	See Note 2

**NOTE 1:** Four USB 3.0 ports are available integrated on the motherboard (2 front, 2 rear). Integrated USB 3.0 ports are supported under Microsoft Windows 7 or Microsoft Windows 8 operating systems only.

**NOTE 2:** Thunderbolt™ 2 is available via an optional add-in card. Thunderbolt is new technology. Thunderbolt cable and Thunderbolt device (sold separately) must be compatible with Windows. To determine whether your device is Thunderbolt Certified for Windows, see <https://thunderbolttechnology.net/products>

#### Networking and Communications

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Integrated Intel I217LM PCIe GbE Controller	Y	N	N	See Notes 1, 2, 3
Intel Ethernet I210-T1 PCIe NIC	Y	Y	E0X95AA	See Notes 3, 4
Intel 6205 802.11 a/b/g/n PCIe x1 WLAN Card	N	Y	E0X93AA	

**NOTE 1:** The integrated network connection is required to support Intel vPro Technology.

**NOTE 2:** If AMT is enabled network teaming with the integrated LAN port is not possible.

**NOTE 3:** "Gigabit" Ethernet indicates compliance with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/sec. For high speed transmission, connection to a

### Supported Components

Gigabit Ethernet server and network infrastructure is required.

**NOTE 4:** The Intel Ethernet I210-T1 PCIe NIC is supported on the following operating systems:

- Microsoft Windows 7 and Windows 8 32-bit and 64-bit versions
- Red Hat Enterprise Linux(RHEL)
- SLED 11.

### Racking and Physical Security

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Solenoid Lock and Hood (SFF) Sensor	Y	Y	E0X97AA	
HP Business PC Security Lock Kit	N	Y	PV606AA	The HP Business PC Security Lock Kit does not work with the Integrated Work Center stand.
HP UltraSlim Cable Lock Kit	N	Y	H4D73AA	

### Input Devices

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP SpacePilot Pro 3D USB Intelligent Controller	N	Y	WH343AA	
HP SpaceMouse Pro USB 3D Input Device	N	Y	B4A20AA	
HP USB 1000dpi Laser Mouse	Y	Y	QY778AA	
HP USB Optical 3-Button Mouse	Y	Y	DY651A	
HP USB Optical Mouse	Y	Y	QY777AA	
HP PS/2 Mouse	Y	Y	QY775AA	
HP 2.4GHz Wireless Keyboard & Mouse	N	Y	NB896AA	
HP USB CCID SmartCard Keyboard	Y	Y	BV813AA	
HP USB Keyboard	Y	Y	QY776AA	
HP PS/2 Keyboard	Y	Y	QY774AA	

### Other Hardware

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Power Cord Kit	N	Y	DM293A	
HP Workstation Mouse Pad	Y	N		Japan

### Supported Components

			only
HP Serial Port Adapter	Y	Y	PA716A
HP ENERGY STAR Qualified Configuration	Y	N	
HP Parallel Port Adapter Kit	N	Y	KD061AA
HP Internal USB Port Kit	N	Y	EM165AA
HP eSATA PCI Cable Kit	Y	Y	FH966AA
HP (SFF) Tower Stand	Y	Y	VN569AA

### Software

	Factory Configured	Option Kit	Support Notes
HP Performance Advisor	Y	N	See Note 1
HP Remote Graphics Software (RGS) 6.0	Y	N	See Note 2
PDF Complete - Corporate Edition	Y	N	
MS Office Home & Business 2013	Y	N	
Cyberlink PowerDVD and Power2Go	Y	N	
HP PC Hardware Diagnostics UEFI	Y	N	Windows OS only

**NOTE 1:** Supports, and preinstalled with, Windows 7 and Windows 8 only. Also available as a free download from [www.hp.com/go/performanceadvisor](http://www.hp.com/go/performanceadvisor)

**NOTE 2:** Supported Operating Systems:

- [Windows 7 Professional](#)
- [Windows 8 Pro](#)
- [RHEL v5.2 - v6.3](#)
- [SLED 11 SP2](#)

### Operating Systems

	Support Notes
Genuine Windows® 7 Ultimate 64-bit	
Genuine Windows® 7 Professional 32-bit	See <a href="http://www.microsoft.com/windows/windows-7/">http://www.microsoft.com/windows/windows-7/</a> for support details.
Genuine Windows® 7 Professional 64-bit	See <a href="http://www.microsoft.com/windows/windows-7/">http://www.microsoft.com/windows/windows-7/</a> for support details.
Genuine Windows® 7 Home Premium 32-bit	See <a href="http://www.microsoft.com/windows/windows-7/">http://www.microsoft.com/windows/windows-7/</a> for support details.
Genuine Windows® 7 Home Premium 64-bit	See <a href="http://www.microsoft.com/windows/windows-7/">http://www.microsoft.com/windows/windows-7/</a> for support details.
Windows 8.1 Pro 64-bit	
Windows 8.1 Simplified Chinese Edition 64-bit	
Windows 8.1 Pro Downgrade to Windows 7 Professional 32-bit	
Windows 8.1 Pro Downgrade to Windows 7 Professional 64-bit	

### Supported Components

Windows 8.1 Pro Downgrade to Windows 7  
Professional 32-bit (National Academic)

Windows 8.1 Pro Downgrade to Windows 7  
Professional 64-bit (National Academic)

HP Linux Installer Kit

See <http://h20331.www2.hp.com/hpsub/cache/537200-0-0-225-121.html>

Red Hat Enterprise Linux (RHEL)  
Workstation - Paper License (1yr)

See <http://www.redhat.com/rhel/desktop/>

SUSE Linux Enterprise Desktop 11

See <http://www.suse.com/products/desktop/>



### System Technical Specifications

System Board		
<b>System Board Form Factor</b>	ATX 24.38 x 24.38 mm (9.6 x 9.6 inches)	
<b>Processor Socket</b>	Single LGA 1150	
<b>CPU Bus Speed</b>	DMI	
<b>Chipset</b>	Intel® PCH C226	
<b>Memory Expansion Slots</b>	4 DDR3 memory slots	
<b>Memory Type Supported</b>	DDR3, UDIMM (Unbuffered), ECC& non-ECC	
<b>Memory Modes</b>	Non-Interleaved for single channel. Interleaved when both channels are populated.	
<b>Memory Speed Supported</b>	1600MHz DDR3	
<b>Memory Protection</b>	ECC available on data	
<b>Maximum Memory</b>	32GB	
<b>Memory Configuration (Supported)</b>	4GB and 8GB non-ECC/ 2GB, 4GB and 8GB ECC unbuffered DIMMs are supported. ECC and non-ECC memory DIMMs cannot be mixed on the same system. <b>NOTE:</b> * Maximum memory capacities assume 64-bit operating systems, such as Genuine Windows® 7 Professional 64-Bit or Red Hat Linux 64-bit. 32-bit Windows Operating Systems support up to 4 GB.	
<b>PCI Express Connectors</b>	<ul style="list-style-type: none"> <li>1 PCI Express Gen3 x16 LP slot (x16 electrical/x16 mechanical)</li> <li>1 PCI Express Gen2 x16 LP slot (x4 electrical/x16 mechanical)</li> <li>1 PCI Express Gen2 x1 LP slot (x1 electrical/x4 mechanical)</li> <li>1 PCI Express Gen2 x1 LP slots (x1 electrical/x1 mechanical)</li> </ul> <b>NOTE:</b> LP = Low Profile  <b>NOTE:</b> In the PCIe Gen3 slot (x16 electrical/x16 mechanical) slot, if it is not being used for a graphics card, only cards certified as After Market Options for this platform are supported.	
<b>Supported Drive Interfaces</b>	<b>SATA</b>	Integrated (5) Serial ATA interfaces (6Gb/s SATA). One port can optionally be used for eSATA. RAID 0 and 1 supported. Factory integrated RAID is Microsoft Windows only.
	<b>Serial Attached SCSI</b>	None
	<b>Integrated RAID</b>	<b>NOTE:</b> Requires identical hard drives (speeds, capacity, interface)
	<b>Integrated Graphics</b>	Integrated Intel HD Graphics 4600 (on Core i5/i7-4xxx processors); Integrated Intel HD Graphics P4600 (on Intel Xeon E3-12x5v3 processors).  Based on Unified Memory Architecture (UMA)- A region of system memory is reserved and dedicated to the graphics display. Support for Microsoft DirectX 11, OpenGL 4.0 and OpenCL 1.2 on Intel HD Graphics P4600; 3 DP 1.2 graphics ports integrated in motherboard; Supports

### System Technical Specifications

		up to three simultaneous displays across DP outputs. Max. resolution supported: 3840x2160 @60Hz
	<b>Network Controller</b>	Integrated Ethernet PHY Connection I217LM. Management capabilities: WOL, PXE 2.1 and AMT 9.0
	<b>External SATA (eSATA)</b>	1 port eSATA capable with optional eSATA After-Market Option cable kit.
	<b>IDE connector</b>	No
	<b>Floppy connector</b>	No
	<b>Serial</b>	1 rear port
	<b>2nd Serial</b>	Yes- requires optional Serial Port Adapter Kit
	<b>Parallel</b>	1 internal header (optional Parallel Port Adapter required)
	<b>CD-ROM input (Audio)</b>	No
	<b>AUX input (Audio)</b>	No
<b>IEEE 1394 Connector(s)</b>	<b>Rear</b>	2 IEEE 1394b (requires optional PCIe 1394b card)
	<b>Internal</b>	No
<b>USB Connector(s)</b>	<b>Front</b>	2 USB 3.0, 2 USB 2.0
	<b>Rear</b>	2 USB 3.0, 4 USB 2.0
	<b>Internal</b>	1 USB 3.0, 2 USB 2.0
<b>HD Integrated Audio</b>	Yes	
<b>Flash ROM</b>	Yes, 16MB	
<b>Chassis Fan Header</b>	Not applicable	
<b>Front Control Panel/Speaker Header</b>	Yes	
<b>CMOS Battery Holder - Lithium</b>	Yes	
<b>Integrated Trusted Platform Module</b>	Integrated TPM 1.2.	
<b>Power Supply Headers</b>	Yes	
<b>Power Switch, Power LED &amp; Hard Drive LED Header</b>	Yes	
<b>Clear Password Jumper</b>	Yes	
<b>Keyboard/Mouse</b>	USB or PS/2	
	<p>240W, 92% efficiency, wide-ranging, active PFC Power Supply;</p> <p>(Note: 240W Standard Efficiency wide-ranging, active PFC Power Supply option available in some countries).</p> <p>The Z230 SFF 92% PSU Efficiency Report can be found at these links:</p> <p><a href="http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD%20COMPANY_PS-4241-1HA_240W_ECOS%203449_Report.pdf">http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD%20COMPANY_PS-4241-1HA_240W_ECOS%203449_Report.pdf</a></p> <p><a href="http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD_D12-">http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD_D12-</a></p>	

### System Technical Specifications

	<a href="#">240P2A 240W ECOS%203384 Report.pdf</a> <a href="http://www.plugloadsolutions.com/psu_reports/Hewlett-Packard%20Company_DPS-240AB-3%20A_240W_ECOS%203416_Report.pdf">http://www.plugloadsolutions.com/psu_reports/Hewlett-Packard%20Company_DPS-240AB-3%20A_240W_ECOS%203416_Report.pdf</a> <a href="http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD%20COMPANY_PCC002-020H2_240W_ECOS%203440_Report.pdf">http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD%20COMPANY_PCC002-020H2_240W_ECOS%203440_Report.pdf</a>
<b>Operating Voltage Range</b>	90-269 VAC
<b>Rated Voltage Range</b>	100-240 VAC
<b>Rated Line Frequency</b>	50-60 Hz
<b>Operating Line Frequency Range</b>	47-63 Hz
<b>Rated Input Current</b>	4A @ 100-240V
<b>Heat Dissipation</b>	Typical: 444 btu/hr (112 kcal/hr) Maximum: 890 btu/hr (224 kcal/hr)
<b>Power Supply Fan</b>	70x25 mm variable speed
<b>ENERGY STAR® qualified (Config Dependent)</b>	Yes
<b>FEMP Standby Power Compliant</b>	Yes, with Wake-on-LAN disabled: <2W in S5- Power Off
<b>Built-in Self Test (BIST) LED</b>	No
<b>Surge Tolerant Full Ranging Power Supply (withstands power surges up to 2000V)</b>	Yes
<b>Hood Lock Header</b>	Yes
<b>ErP Lot 6- Tier 1 Compliance @ 230V (&lt;1W in S5- Power Off)</b>	Yes
<b>ErP Lot 6- Tier 2 Compliance @ 230V (&lt;0.5W in S5- Power Off)</b>	Yes

### System Configurations

<b>Z230 SFF Configuration #1</b>	<b>Processor Info</b>	1x Intel Core i3-4xxx 3.x xMB 2C HT xxW GT1 CPU
	<b>Memory Info</b>	4GB (1x 4GB) 1600 MHz DDR3 non-ECC
	<b>Graphics Info</b>	Intel Integrated Graphics
	<b>Disks/Optical/Floppy</b>	1x SATA 500 GB 7.2k rpm/ 1x DVD-RW
	<b>PSU</b>	240W 92%
	<b>OS /BIOS</b>	--

### System Technical Specifications

Energy Consumption (Watts)		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)						
	Windows Busy Typ (S0)						
	Windows Busy Max (S0)						
	Sleep (S3)						
	Off (S5)						
	Zero Power Mode (EuP)						
Heat Dissipation (Btu/hr)		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)						
	Windows Busy Typ (S0)						
	Windows Busy Max (S0)						
	Sleep (S3)						
	Off (S5)						
	Zero Power Mode (EuP)						

<b>Z230 SFF Configuration #2</b>	<b>Processor Info</b>	1x Intel Xeon E3-1280v3 3.6 8MB 4C HT 84W GT0 CPU
	<b>Memory Info</b>	8GB (2x 4GB) 1600 MHz DDR3 ECC
	<b>Graphics Info</b>	1x NVIDIA Quadro K600 1GB Graphics
	<b>Disks/Optical/Floppy</b>	1x SATA 2 TB 7.2k rpm/ 1xDVD-RW
	<b>PSU</b>	240W 92%
	<b>OS /BIOS</b>	--

Energy Consumption (Watts)		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	32.7 W		32.7 W		32.6 W	
	Windows Busy Typ (S0)	131 W		130 W		130 W	
	Windows Busy Max (S0)	154 W		151 W		155 W	
	Sleep (S3)	2.05 W	1.95 W	2.18 W	2.08 W	2.03 W	1.93 W
	Off (S5)	0.83 W	0.76 W	0.95 W	0.88 W	0.82 W	0.75 W
	Zero Power Mode (EuP)	0.23 W		0.34 W		0.22 W	
Heat Dissipation (Btu/hr)		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	112 btu/hr		112 btu/hr		111 btu/hr	
	Windows Busy Typ (S0)	447 btu/hr		444 btu/hr		444 btu/hr	
	Windows Busy Max (S0)	525 btu/hr		515 btu/hr		529 btu/hr	
	Sleep (S3)	6.99 btu/hr	6.65 btu/hr	7.44 btu/hr	7.10 btu/hr	6.93 btu/hr	6.95 btu/hr
	Off (S5)	2.83 btu/hr	2.59 btu/hr	3.24 btu/hr	3.00 btu/hr	2.80 btu/hr	2.56 btu/hr
	Zero Power Mode (EuP)	0.78 btu/hr		1.16 btu/hr		0.75 btu/hr	

### System Technical Specifications

<b>Z230 SFF Configuration #3</b>	<b>Processor Info</b>	1x Intel Xeon E3-1280v3 3.6 8MB 4C HT 84W GT0 CPU
	<b>Memory Info</b>	32GB (4x 8GB) 1600 MHz DDR3 ECC
	<b>Graphics Info</b>	1x NVIDIA Quadro K600 1GB Graphics
	<b>Disks/Optical/Floppy</b>	2x SATA 2 TB 7.2k rpm/ 1xDVD-RW
	<b>PSU</b>	240W 92%
	<b>OS /BIOS</b>	--

<b>Energy Consumption (Watts)</b>		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	38.8 W		38.7 W		38.9 W	
	Windows Busy Typ (S0)	142 W		140 W		141 W	
	Windows Busy Max (S0)	164 W		161 W		165 W	
	Sleep (S3)	2.87 W	2.75 W	3.01 W	2.90 W	2.86 W	2.75 W
	Off (S5)	0.83 W	0.76 W	0.95 W	0.88 W	0.82 W	0.75 W
	Zero Power Mode (EuP)	0.23 W		0.34 W		0.22 W	
<b>Heat Dissipation (Btu/hr)</b>		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	132 btu/hr		132 btu/hr		133 btu/hr	
	Windows Busy Typ (S0)	485 btu/hr		478 btu/hr		481 btu/hr	
	Windows Busy Max (S0)	560 btu/hr		549 btu/hr		563 btu/hr	
	Sleep (S3)	9.79 btu/hr	9.38 btu/hr	10.3 btu/hr	9.90 btu/hr	9.76 btu/hr	9.38 btu/hr
	Off (S5)	2.83 btu/hr	2.59 btu/hr	3.24 btu/hr	3.00 btu/hr	2.80 btu/hr	2.56 btu/hr
	Zero Power Mode (EuP)	0.78 btu/hr		1.16 btu/hr		0.75 btu/hr	

### Declared Noise Emissions (Entry-level and High-end configurations)

<b>System Configuration (Entry level)</b>	<b>Processor Info</b>	Intel Core i3-4130
	<b>Memory Info</b>	4GB (2x2GB) 1600 MHz
	<b>Graphics Info</b>	Integrated Intel HD Graphics 4400
	<b>Disks/Optical</b>	1x 500 GB 7200 RPM SATA HDD; DVD-RW SuperMulti ODD

<b>Declared Noise Emissions</b> (in accordance with ISO 7779 and ISO 9296)		<b>Sound Power (LWAd, bels)</b>	<b>Deskside Sound Pressure (LpAm, decibels)</b>
	<b>Idle</b>	3.3	
	<b>Hard drive Operating</b> (random reads)	3.3	
	<b>DVD-ROM Operating</b> (sequential reads)		

### System Technical Specifications

<b>System Configuration (High-end)</b>	<b>Processor Info</b>	Intel Xeon E3-1280v3 3.6 GHz
	<b>Memory Info</b>	4 x 4GB DDR3 1600 MHz
	<b>Graphics Info</b>	NVIDIA Quadro K600 graphics
	<b>Disks/Optical</b>	2x 500GB 10K rpm SATA HDDs; SATA Blu-ray ODD

<b>Declared Noise Emissions</b> (in accordance with ISO 7779 and ISO 9296)		<b>Sound Power (LWAd, bels)</b>	<b>Deskside Sound Pressure (LpAm, decibels)</b>
	<b>Idle</b>	3.4	
	<b>Hard drive Operating</b> (random reads)	3.5	
	<b>DVD-ROM Operating</b> (sequential reads)		

<b>Environmental Requirements</b>	<b>Temperature</b>	Operating: 40° to 95° F (5° to 35° C) Non-operating: -40° to 140° F (-40° to 60° C)
	<b>Humidity</b>	Operating: 8% to 85% RH, non-condensing Non-operating: 8% to 90% RH, non-condensing
	<b>Maximum Altitude</b>	Operating: 10,000 feet (3,000 m) Non-operating: 30,000 feet (9,100 m)
	<b>Dynamic (new)</b>	Shock Operating: ½-sine: 40g, 2-3ms Non-operating: ½-sine: 160 cm/s, 2-3ms (~100g) square: 422 cm/s, 20g  Vibration Operating random: 0.5g (rms), 5-300 Hz Non-operating random: 2.0g (rms), 10-500 Hz  <b>NOTES:</b> Values represent individual shock events and do not indicate repetitive shock events. Values do not indicate continuous vibration.
	<b>Cooling</b>	Above 5,000 ft (1524 m) altitude, maximum operating temperature is de-rated by 1.8° F (1° C) per 1,000 ft (305 m) elevation increase

### Physical Security and Serviceability

<b>Access Panel</b>	Tool-less Includes system board and memory information
<b>Hard Drives</b>	Tool-less (Internal bays)
<b>Expansion Cards</b>	Tool-less
<b>Processor Socket</b>	Tool-less, except for the processor heatsink.

### System Technical Specifications

<b>Green User Touch Points</b>	Yes, on tool-free internal chassis mechanisms
<b>Color-coordinated Cables and Connectors</b>	Yes
<b>Memory</b>	Tool-less
<b>System Board</b>	Screw-In
<b>Dual Color Power and HD LED on Front of Computer</b>	Yes
<b>Configuration Record SW</b>	Yes
<b>Over-Temp Warning on Screen</b>	Yes
<b>Restore CD/DVD Set</b>	Consists of an operating system DVD (OSDVD) and a driver DVD (DRDVD). OSDVD restores the original operating system. DRDVD will provide all drivers for the system. The DRDVD may also contain applications that originally shipped with the system for optional installation. Applications can also be obtained from HP.com. OSDVD and DRDVD are orderable with the system and available from HP Support.
<b>Dual Function Front Power Switch</b>	Yes, causes a fail-safe power off when held for 4 seconds
<b>Padlock Support</b>	Yes (optional): Locks side cover and secures chassis from theft 0.22-in diameter padlock loop at rear of system
<b>Cable Lock Support</b>	Yes, Kensington Cable Lock (optional): Locks side cover and secures chassis from theft 3 mm x 7 mm slot at rear of system
<b>Universal Chassis Clamp Lock Support</b>	Yes (optional): Locks side cover and locks cables to chassis. Secures chassis from theft and allows multiple units to be chained together when used with optional cable Threaded feature at rear of system
<b>Solenoid Lock and Hood Sensor</b>	Yes (optional) The Solenoid Hood Lock eliminates the need for a physical key by making the chassis lockable through software and a password. You can also lock and unlock the chassis remotely over the network. The Sensor Kit detects when the access panel has been removed.
<b>Rear Port Control Cover</b>	Yes, locks rear I/O cables to prevent cable theft
<b>Serial, Parallel, USB, Audio, Network, Enable/Disable Port Control</b>	Yes, enables or disables serial, USB, audio, and network ports
<b>Removable Media Write/Boot Control</b>	Yes, prevents ability to boot from removable media on supported devices (and can disable writes to media)
<b>Power-On Password</b>	Yes, prevents an unauthorized person from booting up the workstation
<b>Setup Password</b>	Yes, prevents an unauthorized person from changing the workstation configuration
<b>3.3V Aux Power LED on System PCA</b>	Yes
<b>NIC LEDs (integrated) (Green &amp; Amber)</b>	Yes
<b>CPUs and Heatsinks</b>	A T-15 Torx or flat blade screwdriver is needed to remove the CPU heatsink before the CPU can be removed. CPU removal is tool-less
<b>Power Supply Diagnostic</b>	No

### System Technical Specifications

<b>LED</b>	
<b>Front Power Button</b>	Yes, ACPI multi-function
<b>Front Power LED</b>	Yes, blue (normal), red (fault)
<b>Front Hard Drive Activity LED</b>	Yes, green
<b>Front ODD Activity LED</b>	Yes
<b>Internal Speaker</b>	Yes
<b>System/Emergency ROM Flash Recovery</b>	Recovers corrupted system BIOS.
<b>Cooling Solutions</b>	Air cooled forced convection
<b>Power Supply Fans</b>	70mm x 70mm x 25mm 4-wire PWM (non-serviceable)
<b>CPU Heatsink Fan</b>	Not applicable- CPU heatsink is passive.
<b>Chassis Fan</b>	Not applicable. CPU heatsink fan also operates as the chassis fan.
<b>Memory Heatsink Fan</b>	No
<b>HP PC Hardware Diagnostics UEFI</b>	HP PC Hardware Diagnostics (UEFI) enables hardware level testing outside the operating system on many components. The diagnostics can be invoked by pressing F2 at POST, and is available as a download from HP Support.
<b>Access Panel Key Lock</b>	No
<b>ACPI-Ready Hardware</b>	Advanced Configuration and Power Management Interface (ACPI). <ul style="list-style-type: none"> <li>Allows the system to wake from a low power mode.</li> <li>Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system</li> </ul>
<b>Trusted Platform Module Chip with optional ProtectTools Software</b>	Yes
<b>Integrated Chassis Handles</b>	No
<b>Power Supply</b>	Requires T15 Torx or flat blade screwdriver
<b>PCI Card Retention</b>	Yes, rear (all), middle (none), front (none)
<b>Flash ROM</b>	Yes
<b>Diagnostic Power Switch LED on board</b>	Yes
<b>Clear Password Jumper</b>	Yes
<b>Clear CMOS Button</b>	Yes
<b>CMOS Battery Holder</b>	Yes
<b>DIMM Connectors</b>	Yes
<b>HP ProtectTools Security Manager</b>	Yes - Not supported on Microsoft XP x64 or Linux



### System Technical Specifications

<b>BIOS</b>	
<b>BIOS 32-bit Services</b>	Standard BIOS 32-bit Service Directory Proposal v0.4
<b>PCI 3.0 Support</b>	Full BIOS support for PCI Express through industry standard interfaces.
<b>ATAPI</b>	ATAPI Removable Media Device BIOS Specification Version 1.0.
<b>BBS</b>	BIOS Boot Specification v1.01. Provides more control over how and from what devices the workstation will boot.
<b>WMI Support</b>	WMI is Microsoft's implementation of Web-Based Enterprise Management (WBEM) for Windows. WMI is fully compliant with the Distributed Management Task Force (DMTF) Common Information Model (CIM) and WBEM specifications.
<b>BIOS Power On</b>	Users can define a specific day-of-week and time for the system to power on.
<b>ROM Based Computer Setup Utility (F10)</b>	Review and customize system configuration settings controlled by the BIOS.
<b>System/Emergency ROM Flash Recovery with Video</b>	Recovers system BIOS in corrupted Flash ROM.
<b>Replicated Setup</b>	Saves BIOS settings to USB flash device in human readable file. Repset.exe utility can then replicate these settings on machines being deployed without entering Computer Configuration Utility (F10 Setup).
<b>SMBIOS</b>	System Management BIOS 2.7.1, for system management information.
<b>Boot Control</b>	Disables the ability to boot from removable media on supported devices.
<b>Memory Change Alert</b>	Alerts management console if memory is removed or changed.
<b>Thermal Alert</b>	Monitors the temperature state within the chassis. Three modes: <ul style="list-style-type: none"> <li>• NORMAL - normal temperature ranges.</li> <li>• ALERTED - excessive temperatures are detected. Raises a flag so action can be taken to avoid shutdown or provide for a smoother system shutdown.</li> <li>• SHUTDOWN - excessive temperatures are encountered. Automatically shuts down the computer without warning before hardware component damage occurs.</li> </ul>
<b>Remote ROM Flash</b>	Provides secure, fail-safe ROM image management from a central network console. Updates can be performed before starting the OS. Updates can be periodically scheduled.
<b>ACPI (Advanced Configuration and Power Management Interface)</b>	Allows the system to enter and resume from low power modes (sleep states). Enables an operating system to control system power consumption based on the dynamic workload. Makes it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system. Supports ACPI 4.0 for full compatibility with 64-bit operating systems.
<b>Ownership Tag</b>	A user-defined string stored in non-volatile memory that is displayed in the BIOS splash screen.
<b>Remote Wakeup/Remote Shutdown</b>	System administrators can power on, restart, and power off a client computer from a remote location.
<b>ASF 2.0 Compliant</b>	No.
<b>Instantly Available PC (Suspend to RAM - ACPI sleep state S3)</b>	Allows for very low power consumption with quick resume time.

### System Technical Specifications

<b>Remote System Installation via F12 (PXE 2.1) (Remote Boot from Server)</b>	Allows a new or existing system to boot over the network and download software, including the operating system.
<b>ROM revision levels</b>	Reports the system BIOS revision level in Computer Configuration Utility (F10 Setup). Version is available through an industry standard interface (SMBIOS) so that management SW applications can use and report this information.
<b>System board revision level</b>	Allows management SW to read revision level of the system board. Revision level is digitally encoded into the HW and cannot be modified.
<b>Start-up Diagnostics (Power-on Self-Test)</b>	Assesses system health at boot time with selectable levels of testing.
<b>Auto Setup when new hardware installed</b>	System automatically detects addition of new hardware.
<b>Keyboard-less Operation</b>	The system can be booted without a keyboard.
<b>Localized ROM Setup</b>	Common BIOS image supports System Configuration Utility (F10 Setup) menus in 12 languages with local keyboard mappings.
<b>Asset Tag</b>	The user or IT administrator to set a unique tag string in non-volatile memory.
<b>Per-slot Control</b>	Allows I/O slot parameters (option ROM enable/disable) to be configured individually.
<b>Adaptive Cooling</b>	Control parameters are set according to detected hardware configuration for optimal acoustics.
<b>Pre-boot Diagnostics</b>	(Pre-video) critical errors are reported via beeps and blinks on the power LED.
<b>Intel® Active Management Technology (AMT)</b>	AMT 9.0; Allows workstation status to be monitored on a remote console
<b>Digitally and Cryptographically Signed BIOS</b>	Helps to prevent the installation of unauthorized versions of a BIOS (a rogue BIOS) from a virus, malware, or other code that could lead to compromised system security, data access, physical service, or even system board replacement.
<b>Master Boot Record Protection</b>	A feature in the HP BIOS that prevents changes and/or infections to the Master Boot Record. Useful in protecting from viruses.
<b>Boot Block Emergency Recovery Mode (BIOS Recovery)</b>	The HP BIOS offers a write-protected boot block ROM that provides recovery from a failed flashing of the computer BIOS. This special recovery mode prevents the system from becoming unusable or "bricked" when a BIOS update is interrupted.
<b>Industry Standard Specification Support</b>	
<b>Industry Standard</b>	Revision Supported by the BIOS
<b>UEFI Specification Revision</b>	UEFI 2.3.1
<b>ACPI</b>	Advanced Configuration and Power Management Interface, Version 4.0
<b>ASF</b>	Alert Standard Format Specification, Version 2.0
<b>ATA (IDE)</b>	AT Attachment 6 with Packet Interface (ATA/ATAPI-6), Revision 3b
<b>CD Boot</b>	"El Torito" Bootable CD-ROM Format Specification Version 1.0
<b>EDD</b>	- Enhanced Disk Drive Specification Version 1.1 - BIOS Enhanced Disk Drive Specification Version 3.0
<b>EHCI</b>	Enhanced Host Controller Interface for Universal Serial Bus, Revision 1.0

### System Technical Specifications

<b>PCI</b>	PCI Local Bus Specification, Revision 2.3 PCI Power Management Specification, Revision 1.1 PCI Firmware Specification, Revision 3.0
<b>PCI Express</b>	PCI Express Base Specification, Revision 2.0; PCI Express Base Specification, Revision 3.0.
<b>PMM</b>	POST Memory Manager Specification, Version 1.01
<b>SATA</b>	- Serial ATA Specification, Revision 1.0a - Serial ATAII: Extensions to Serial ATA 1.0, Revision 1.0a - Serial ATAII Cables and Connectors Volume 2 Gold - SATA-IO SATA Revision 3.0 Specification
<b>SPD</b>	PC SDRAM Serial Presence Detect (SPD) Specification, Revision 1.2B
<b>TPM</b>	Trusted Computing Group TPM Specification Version 1.2
<b>USB</b>	Universal Serial Bus Revision 1.1 Specification Universal Serial Bus Revision 2.0 Specification Universal Serial Bus Revision 3.0 Specification

### Social and Environmental Responsibility

<b>Eco-Label Certifications &amp; Declarations</b>	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: <ul style="list-style-type: none"> <li>ENERGY STAR® (energy-saving features available on selected configurations -Windows only)</li> <li>US Federal Energy Management Program (FEMP)</li> <li>China Energy Conservation Program (CECP)</li> <li>IT ECO declaration</li> </ul>
<b>Batteries</b>	The battery in this product complies with EU Directive 2006/66/EC Battery size: CR2032 (coin cell) Battery type: Lithium Metal  The battery in this product does not contain: <ul style="list-style-type: none"> <li>Mercury greater than 5ppm by weight</li> <li>Cadmium greater than 10ppm by weight</li> <li>Lead greater than 40ppm by weight</li> </ul>
<b>Restricted Material Usage</b>	This product meets the material restrictions specified in HP's General Specification for the Environment. <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/qse.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/qse.pdf</a> Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis.
<b>Low Halogen Statement</b>	This product is low halogen except for power cords, cables and peripherals, as well as the following customer-configurable internal components: Creative Recon3D PCIe Audio Card is not Low Halogen. Service parts obtained after purchase may not be Low Halogen.
<b>End-of-Life Management</b>	Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic

### System Technical Specifications

<b>and Recycling</b>	areas. To recycle your product, please go to: <a href="http://www.hp.com/recycle">http://www.hp.com/recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner. This product is greater than 90% recyclable by weight when properly disposed of at end of life.
<b>Hewlett-Packard Corporate Environmental Information</b>	For more information about HP's commitment to the environment: Global Citizenship Report <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a>  Eco-label certifications <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html">http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html</a>  ISO 14001 certificates: <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html">http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html</a>
<b>Additional Information</b>	<ul style="list-style-type: none"> <li>• This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.</li> <li>• Plastic parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.</li> <li>• This product is &gt;90% recycle-able when properly disposed of at end of life</li> <li>• EPEAT Gold registered in the U.S. EPEAT registration varies by country. See <a href="http://www.epeat.net">www.epeat.net</a> for registration status by country.</li> </ul>
<b>Packaging</b>	<p>HP Workstation product packaging meets the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/society/gen_specifications.html">http://www.hp.com/hpinfo/globalcitizenship/society/gen_specifications.html</a></p> <ul style="list-style-type: none"> <li>• Does not contain restricted substances listed in HP Standard 011-1 General Specification for the Environment</li> <li>• Does not contain ozone-depleting substances (ODS)</li> <li>• Does not contain heavy metals (lead, mercury, cadmium or hexavalent chromium) in excess of 100 ppm sum total for all heavy metals listed</li> <li>• Maximizes the use of post-consumer recycled content materials in packaging materials</li> <li>• All packaging material is recyclable</li> <li>• All packaging material is designed for ease of disassembly</li> <li>• Reduced size and weight of packages to improve transportation fuel efficiency</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards formatting</li> </ul>
<b>Packaging Materials</b>	
<b>Internal</b>	Cushions made from fabricated recycled expanded-polyethylene (EPE) or recycled expanded-polypropylene (EPP). May also be made from recycled molded paper-pulp (MPP).
<b>External</b>	Carton made from corrugated fiberboard with at least 25% recycled content.

### Manageability

<b>Intel Active Management Technology (AMT)</b>	<p>An advanced set of remote management features and functionality which provides network administrators the latest and most effective tools to remotely discover, heal, and protect networked client systems regardless of the system's health or power state. AMT 8.0 includes the following advanced management functions:</p> <ul style="list-style-type: none"> <li>• Power Management (on, off, reset)</li> <li>• Hardware Inventory (includes BIOS and firmware revisions)</li> </ul>
---	--

### System Technical Specifications

	<ul style="list-style-type: none"> <li>• Hardware Alerting</li> <li>• Agent Presence</li> <li>• System Defense Filters</li> <li>• SOL/IDER</li> <li>• Cisco NAC/SDN Support</li> <li>• ME Wake-on-LAN</li> <li>• DASH 1.1 compliance</li> <li>• IPv6 Support</li> <li>• Fast Call for Help - a client inside or outside the firewall may initiate a call for help via BIOS screen, periodic connections, or alert triggered connection</li> <li>• Remote Scheduled Maintenance - pre-schedule when the PC connects to the IT or service provider console for maintenance. Remote PCs can get required patches, be inventoried, etc by connecting to their IT console or Service Provider when it's convenient</li> <li>• Remote Alerts - automatically alert IT or service provider if issues arise</li> <li>• Access Monitor - Provides oversight into Intel® AMT actions to support security requirements</li> <li>• PC Alarm Clock</li> <li>• Microsoft NAP Support</li> <li>• Host Base set-up and configuration</li> <li>• Management Engine (ME) firmware roll back</li> <li>• Wireless AMT functionality on Desktop (WoDT)</li> <li>• Enhanced KVM resolution</li> </ul>
<b>Intel® vPro™ Technology</b>	The HP Z230 workstations support Intel vPro technology when purchased with a vPro technology capable CPU: Intel® Xeon® processor E3-1200v2 family or 3rd Generation Intel Core i5/i7 processors with Intel VT and Intel TXT technology
<b>Remote Manageability Software Solutions</b>	Visit: <a href="http://www.hp.com/go/easydeploy">http://www.hp.com/go/easydeploy</a>
<b>System Software Manager</b>	Visit: <a href="http://www.hp.com/go/ssm">http://www.hp.com/go/ssm</a>
<b>Service, Support, and Warranty</b>	<ul style="list-style-type: none"> <li>• Program to proactively communicate Product Change Notifications (PCNs) and Customer Advisories by email to customers, based on a user-defined profile.</li> <li>• PCNs provide advance notification of hardware and software changes to be implemented in the factory providing time to plan for transition.</li> <li>• Customer Advisories provide concise, effective problem resolution, greatly reducing the need to call technical support.</li> </ul>

## Technical Specifications - Processors

Intel® Xeon® processor E3-1281v3, Quad-Core, 8 MB cache, 3.7 GHz, up to 4.1 GHz with Intel Turbo Boost Technology  
Intel® Xeon® processor E3-1280v3, Quad-Core, 8 MB cache, 3.6 GHz, up to 4.0 GHz with Intel Turbo Boost Technology  
Intel® Xeon® processor E3-1271v3, Quad-Core, 8 MB cache, 3.6 GHz, up to 4.0GHz with Intel Turbo Boost Technology  
Intel® Xeon® processor E3-1270v3, Quad-Core, 8 MB cache, 3.5 GHz, up to 3.9 GHz with Intel Turbo Boost Technology  
Intel® Xeon® processor E3-1246v3, Quad-Core, 8 MB cache, 3.5 GHz, up to 3.9 GHz with Intel Turbo Boost Technology  
Intel® Xeon® processor E3-1245v3, Quad-Core, 8 MB cache, 3.4 GHz, up to 3.8 GHz with Intel Turbo Boost Technology  
Intel® Xeon® processor E3-1241v3, Quad-Core, 8 MB cache, 3.5 GHz, up to 3.9 GHz with Intel Turbo Boost Technology  
Intel® Xeon® processor E3-1240v3, Quad-Core, 8 MB cache, 3.4 GHz, up to 3.8 GHz with Intel Turbo Boost Technology  
Intel® Xeon® processor E3-1231v3, Quad-Core, 8 MB cache, 3.4 GHz, up to 3.8 GHz with Intel Turbo Boost Technology  
Intel® Xeon® processor E3-1230v3, Quad-Core, 8 MB cache, 3.3 GHz, up to 3.7 GHz with Intel Turbo Boost Technology  
Intel® Xeon® processor E3-1226v3, Quad-Core, 8 MB cache, 3.3 GHz, up to 3.7 GHz with Intel Turbo Boost Technology  
Intel® Xeon® processor E3-1225v3, Quad-Core, 8 MB cache, 3.2 GHz, up to 3.6 GHz with Intel Turbo Boost Technology

---

Intel® Core™ i7-4790 processor, Quad-Core, 8 MB cache, 3.6 GHz, up to 4.0 GHz with Intel Turbo Boost Technology  
Intel® Core™ i7-4771 processor, Quad-Core, 8 MB cache, 3.5 GHz, up to 3.9 GHz with Intel Turbo Boost Technology  
Intel® Core™ i7-4770 processor, Quad-Core, 8 MB cache, 3.4 GHz, up to 3.9 GHz with Intel Turbo Boost Technology  
Intel® Core™ i5-4690 processor, Quad-Core, 6 MB cache, 3.5 GHz, up to 3.9 GHz with Intel Turbo Boost Technology  
Intel® Core™ i5-4670 processor, Quad-Core, 6 MB cache, 3.4 GHz, up to 3.8 GHz with Intel Turbo Boost Technology  
Intel® Core™ i5-4590 processor, Quad-Core, 6 MB cache, 3.3 GHz, up to 3.7 GHz with Intel Turbo Boost Technology  
Intel® Core™ i5-4570 processor, Quad-Core, 6 MB cache, 3.2 GHz, up to 3.6 GHz with Intel Turbo Boost Technology  
Intel® Core™ i3-4350 processor, Dual-Core, 4 MB cache, 3.6 GHz  
Intel® Core™ i3-4330 processor, Dual-Core, 4 MB cache, 3.5 GHz  
Intel® Core™ i3-4150 processor, Dual-Core, 4 MB cache, 3.5 GHz  
Intel® Core™ i3-4130 processor, Dual-Core, 4 MB cache, 3.4 GHz

---

Intel® Pentium® G3220 processor, Dual-Core, 3 MB cache, 3.0 GHz  
Intel® Pentium® G3240 processor, Dual-Core, 3 MB cache, 3.1 GHz

### Technical Specifications - Hard Drives

<b>SATA Hard Drives for HP Workstations</b>	<b>250GB SATA 10K rpm SFF HDD</b>	<b>Capacity</b>	250GB	
		<b>Height</b>	0.6 in; 1.53 cm	
		<b>Width</b>	<b>Media Diameter</b>	2.5 in; 6.36 cm
			<b>Physical Size</b>	2.75 in; 6.99 cm
		<b>Interface</b>	Serial ATA (6Gb/s)	
		<b>Synchronous Transfer Rate (Maximum)</b>	Up to 600MB/s	
		<b>Buffer</b>	64MB	
		<b>Cache</b>	Adaptive	
		<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b>	1.2ms (typical)
			<b>Average</b>	3.6ms
			<b>Full Stroke</b>	9.0ms (typical)
		<b>Rotational Speed</b>	10K rpm	
		<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	
	<b>500GB SATA 10K rpm SFF HDD</b>	<b>Capacity</b>	500GB	
		<b>Height</b>	0.6 in; 1.53 cm	
		<b>Width</b>	<b>Media Diameter</b>	2.5 in; 6.36 cm
			<b>Physical Size</b>	2.75 in; 6.99 cm
		<b>Interface</b>	Serial ATA (6Gb/s)	
		<b>Synchronous Transfer Rate (Maximum)</b>	Up to 600MB/s	
		<b>Buffer</b>	64MB	
		<b>Cache</b>	Adaptive	
		<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b>	1.2ms (typical)
			<b>Average</b>	3.6ms
			<b>Full Stroke</b>	9.0ms (typical)
		<b>Rotational Speed</b>	10K rpm	
		<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	
	<b>1TB SATA 10K rpm SFF HDD</b>	<b>Capacity</b>	1TB	
		<b>Height</b>	0.6 in; 1.53 cm	
		<b>Width</b>	<b>Media Diameter</b>	2.5 in; 6.36 cm
			<b>Physical Size</b>	2.75 in; 6.99 cm
		<b>Interface</b>	Serial ATA (6Gb/s)	
		<b>Synchronous Transfer Rate (Maximum)</b>	Up to 600MB/s	
		<b>Buffer</b>	64MB	

### Technical Specifications - Hard Drives

	<b>Cache</b>	Adaptive	
	<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b>	1.2ms (typical)
		<b>Average</b>	3.6ms
		<b>Full Stroke</b>	9.0ms (typical)
	<b>Rotational Speed</b>	10K rpm	
	<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	
<b>500GB SATA 7200 rpm 6Gb/s 3.5" HDD</b>	<b>Capacity</b>	500GB	
	<b>Height</b>	1 in; 2.54 cm	
	<b>Width</b>	<b>Media Diameter</b>	3.5 in; 8.9 cm
		<b>Physical Size</b>	4 in; 10.17 cm
	<b>Interface</b>	Serial ATA (6.0Gb/s), NCQ enabled	
	<b>Synchronous Transfer Rate</b> (Maximum)	Up to 600MB/s	
	<b>Buffer</b>	16MB	
	<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b>	2 ms
		<b>Average</b>	11 ms
		<b>Full Stroke</b>	21 ms
	<b>Rotational Speed</b>	7,200 rpm	
	<b>Logical Blocks</b>	976,773,168	
	<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	
<b>1TB SATA 7200 rpm 6Gb/s 3.5" HDD</b>	<b>Capacity</b>	1 Terabyte (1000 GB)	
	<b>Height</b>	1 in; 2.54 cm	
	<b>Width</b>	<b>Media Diameter</b>	3.5 in; 8.9 cm
		<b>Physical Size</b>	4 in; 10.17 cm
	<b>Interface</b>	Serial ATA (6.0Gb/s), NCQ enabled	
	<b>Synchronous Transfer Rate</b> (Maximum)	Up to 600 MB/s	
	<b>Buffer</b>	32MB	
	<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b>	2 ms
		<b>Average</b>	11 ms
		<b>Full Stroke</b>	21 ms
	<b>Rotational Speed</b>	7,200 rpm	
	<b>Logical Blocks</b>	1,953,525,168	
	<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	
<b>2.0TB SATA 7200 rpm</b>	<b>Capacity</b>	2TB	



### Technical Specifications - Hard Drives

#### 6Gb/s 3.5" HDD

<b>Height</b>	1 in; 2.54 cm
<b>Width</b>	<b>Media Diameter</b> 3.5 in; 8.9 cm
	<b>Physical Size</b> 4 in; 10.17 cm
<b>Interface</b>	Serial ATA (6.0 Gb/s), NCQ Enabled
<b>Synchronous Transfer Rate (Maximum)</b>	Up to 600MB/s
<b>Buffer</b>	64MB
<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b> 1.0 ms
	<b>Average</b> 11 ms
	<b>Full Stroke</b> 18 ms
<b>Rotational Speed</b>	7,200 rpm
<b>Logical Blocks</b>	3,907,029,168
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)

#### 3.0TB SATA 7200 rpm 6Gb/s 3.5" HDD

<b>Capacity</b>	3.0TB
<b>Height</b>	1 in; 2.54 cm
<b>Width</b>	<b>Media Diameter</b> 3.5 in; 8.9 cm
	<b>Physical Size</b> 4.0 in; 10.17 cm
<b>Interface</b>	Serial ATA (6.0Gb/s), NCQ enabled
<b>Synchronous Transfer Rate (Maximum)</b>	Up to 6.0 Gb/s
<b>Buffer</b>	64MB
<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b> 0.6 ms
	<b>Average</b> 11 ms
	<b>Full Stroke</b> Not specified
<b>Rotational Speed</b>	7200 rpm
<b>Operating Temperature</b>	41° to 140° F (5° to 60° C)

#### 500GB SATA 7.2K SED SFF HDD

<b>Capacity</b>	500GB
<b>Height</b>	0.275 in; 0.7 cm
<b>Width</b>	<b>Media Diameter</b> 2.5 in; 6.36 cm
	<b>Physical Size</b> 2.75 in; 6.99 cm
<b>Interface</b>	Serial ATA (6Gb/s)
<b>Synchronous Transfer Rate (Maximum)</b>	Up to 600MB/s
<b>Buffer</b>	32MB
<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b> 1ms
	<b>Average</b> 4.2ms
	<b>Full Stroke</b> 25ms (typical)

### Technical Specifications - Hard Drives

<b>HP Solid State Drives (SSDs) for Workstations</b>	<b>HP 128GB SATA 6Gb/s SSD</b>	<b>Rotational Speed</b>	7,200 rpm
		<b>Operating Temperature</b>	32° to 140° F (0° to 60° C)
		<b>Capacity</b>	128GB
		<b>Height</b>	0.28 in; 0.7 cm
		<b>Width</b>	<b>Physical Size</b> 2.5 in; 6.36 cm
		<b>Interface</b>	SATA 6Gb/s
		<b>Synchronous Transfer Rate (Maximum)</b>	Up to 500MB/s (Sequential Read)
		<b>Operating Temperature</b>	32° to 158° F (0° to 70° C)
	<b>HP 256GB SATA 6Gb/s SSD</b>	<b>Capacity</b>	256GB
		<b>Height</b>	0.28 in; 0.7 cm
		<b>Interface</b>	SATA 6Gb/s
		<b>Synchronous Transfer Rate (Maximum)</b>	Up to 500MB/s (Sequential Read)
		<b>Operating Temperature</b>	32° to 158° F (0° to 70° C)
	<b>HP 512GB SATA 6Gb/s SSD</b>	<b>Capacity</b>	512GB
		<b>Height</b>	0.28 in; 0.7 cm
		<b>Width</b>	<b>Physical Size</b> 2.5 in; 6.36 cm
		<b>Interface</b>	6Gb/s SATA
		<b>Synchronous Transfer Rate (Maximum)</b>	Up to 500MB/s (Sequential Read)
		<b>Operating Temperature</b>	32° to 158° F (0° to 70° C)
	<b>HP 1TB SATA 6Gb/s SSD</b>	<b>Capacity</b>	1TB
		<b>Height</b>	0.28 in; 0.7 cm
		<b>Width</b>	<b>Physical Size</b> 2.5 in; 6.36 cm
		<b>Interface</b>	6Gb/s SATA
		<b>Synchronous Transfer Rate (Maximum)</b>	Up to 500MB/s (Sequential Read)
		<b>Operating Temperature</b>	32° to 158° F (0° to 70° C)
	<b>HP 256GB SATA 6Gb/s SED SSD</b>	<b>Capacity</b>	256GB
		<b>Height</b>	0.28 in; 0.7 cm
		<b>Width</b>	<b>Physical Size</b> 2.5 in; 6.36 cm
		<b>Interface</b>	6Gb/s SATA
		<b>Synchronous Transfer Rate (Maximum)</b>	Up to 550MB/s (Sequential Read)
		<b>Operating Temperature</b>	32° to 158° F (0° to 70° C)

### Technical Specifications - Hard Drives

	<b>Intel Pro 1500 180GB SATA SSD</b>	<b>Capacity</b>	180GB	
		<b>Width</b>	<b>Physical Size</b>	2.5 in; 6.36 cm
		<b>Interface</b>	6Gb/s SATA	
		<b>Synchronous Transfer Rate (Maximum)</b>	600 Mb/s	
	<b>Samsung Enterprise 240GB SATA SSD</b>	<b>Capacity</b>	240GB	
		<b>Width</b>	<b>Physical Size</b>	2.5 in; 6.36 cm
		<b>Interface</b>	SATA 6Gb/s	
		<b>Synchronous Transfer Rate (Maximum)</b>	Up to 600MB/s	
	<b>Samsung Enterprise 480GB SATA SSD</b>	<b>Capacity</b>	480GB	
		<b>Width</b>	<b>Physical Size</b>	2.5 in; 6.36 cm
		<b>Interface</b>	SATA 6Gb/s	
		<b>Synchronous Transfer Rate (Maximum)</b>	Up to 600MB/s	
<b>PCIe SSDs for HP Workstations</b>	<b>HP Z Turbo Drive 256GB SSD</b>	<b>Capacity</b>	256GB	
		<b>Interface</b>	PCI Express 2.0 x4 electrical x4 physical	
		<b>Operating Temperature</b>	32° to 158° F (0° to 70° C)	
	<b>HP Z Turbo Drive 512GB SSD</b>	<b>Capacity</b>	512GB	
		<b>Interface</b>	PCI Express 2.0 x4 electrical x4 physical	
		<b>Operating Temperature</b>	32° to 158° F (0° to 70° C)	

### Technical Specifications - Graphics

#### NVIDIA NVS 310 512MB Graphics

##### Form Factor

Low Profile:  
2.713 inches in height × 6.150 inches in length

##### Graphics Controller

NVIDIA NVS 310

##### Bus Type

PCI Express x16, 2.0 compliant

##### Memory

Size: 512MB DDR3  
Clock: 875Mhz  
Memory Bandwidth: 14GB/s

##### Connectors

2 × DisplayPort 1.2

##### Maximum Resolution

Up to 2560 × 1600 (digital display) per display.

##### Image Quality Features

See Display Output section.

The following video formats are supported:

- MPEG2
- MPEG4 Part 2 Advanced Simple Profile
- H.264 SVC codec support
- Support for 3D Blu Ray
- VC1
- DivX version 3.11 and later
- MVC

A full range of video resolutions are supported including 1080p, 1080i, 720p, 480p and 480i. The NVS 310 GPU provides hardware acceleration for the computationally intensive parts of video processing, as well as provides improved video playback speeds via faster decode and transcode.

#### Display Output

Up to 2 displays in the following configurations:

DisplayPort output:

- Drives two DisplayPort enabled digital display at resolutions up to 2560 × 1600 at 60 Hz with reduced blanking, when connected natively using the 2 DisplayPort connectors on the NVS 310 graphics card
- Supports 2 monitors up to resolution of 1920 × 1200 at 60 Hz with reduced blanking using DisplayPort 1.2 multi stream topology technology.

DVI-D output:

- Drives two digital display at resolutions up to 1920 × 1200 at 60 Hz with reduced blanking using DisplayPort to DVI-D single-link cable adaptors
- Drives two digital display at resolutions up to 2560 × 1600 at 60 Hz with reduced blanking using DisplayPort to DVI-D dual-link cable adaptors

### Technical Specifications - Graphics

#### HDMI output:

- NVS 310 is capable of driving two high definition (HD) panels up to resolutions of 1920 × 1080P at 60 Hz using DisplayPort to HDMI cable adaptors

#### VGA display output:

- Drives two analog display at resolutions up to 1920 × 1200 at 60 Hz using DisplayPort to VGA cable adaptors

#### Shading Architecture

Shader Model 5.0

#### Supported Graphics APIs

DX11, OpenGL 4.1

#### Available Graphics Drivers

Genuine Windows 7 Professional (64-bit and 32-bit)  
Microsoft Windows XP Professional (64-bit and 32-bit)  
Red Hat Enterprise Linux(RHEL)  
SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or the latest HP qualified drivers are available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

SUSE Linux Enterprise drivers may also be obtained from:

<ftp://download.nvidia.com/novell> or <http://www.nvidia.com>

#### Power Consumption

19.5 Watts

#### Note

The thermal solution used on this card is an active fan heatsink.

#### NVIDIA NVS 315 1GB Graphics (for HP Workstations)

#### Form Factor

Low Profile:  
2.713 inches in height × 5.7 inches in length

#### Graphics Controller

NVIDIA NVS 315 (using GF119-825 GPU)  
Number of Cores: 48 CUDA cores  
Max. Power: 19.3W  
Cooling Solution: Active fan heatsink

#### Bus Type

PCI Express x16, 2.0 compliant

#### Memory

Size: 1GB DDR3  
Clock: 875Mhz  
Memory Bandwidth: 14GB/s

#### Connectors

DMS-59 output

Cables included:

- For CTO: DMS-59 to DVI cable
- For AM0: DMS-59 to DVI cable and DMS-59 to VGA cable

#### Maximum Resolution

Maximum number of displays supported: 2

Maximum Resolution Support:

### Technical Specifications - Graphics

	<ul style="list-style-type: none"> <li>- DMS-59 to VGA: 2048 x 1536 @ 85Hz</li> <li>- DMS-59 to DVI: 1980 x 1200 @ 60Hz</li> <li>- DMS-59 to DP: 2560 x 1600 @ 60Hz</li> </ul>
<b>Image Quality Features</b>	See Display Output section.
	<p>The following video formats are supported:</p> <ul style="list-style-type: none"> <li>- MPEG2</li> <li>- MPEG4 Part 2 Advanced Simple Profile</li> <li>- H.264 SVC codec support</li> <li>- Support for 3D Blu Ray</li> <li>- VC1</li> <li>- DivX version 3.11 or later</li> </ul>
<b>Display Output</b>	<p>A full range of video resolutions are supported including 1080p, 1080i, 720p, 480p and 480i. The NVS 315 GPU provides hardware acceleration for the computationally intensive parts of video processing, as well as provides improved video playback speeds via faster decode and transcode.</p> <p>Up to 2 displays in the following configurations:</p> <p>DisplayPort output:</p> <ul style="list-style-type: none"> <li>• Drives two DisplayPort enabled digital displays at resolutions up to 2560 x 1600 at 60 Hz with reduced blanking, when connected via the DMS-59 to DP adapter.</li> </ul> <p>DVI-D output:</p> <ul style="list-style-type: none"> <li>• Drives two digital display at resolutions up to 1920 x 1200 at 60 Hz with reduced blanking using DMS-59 to DVI-D single-link cable adaptor</li> </ul> <p>VGA display output:</p> <ul style="list-style-type: none"> <li>• Drives two analog display at resolutions up to 2048 x 1536 at 85 Hz using DMS-59 to VGA cable adaptor.</li> </ul>
<b>Shading Architecture</b>	Shader Model 5.0
<b>Supported Graphics APIs</b>	DX11, OpenGL 4.3
<b>Available Graphics Drivers</b>	<p>Microsoft Windows 8</p> <p>Microsoft Windows 7 Professional (64-bit and 32-bit)</p> <p>Microsoft Windows XP Professional (64-bit and 32-bit)</p> <p>Red Hat Enterprise Linux(RHEL)</p> <p>SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)</p>

HP qualified drivers may be preloaded or the latest HP qualified drivers are

### Technical Specifications - Graphics

available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

SUSE Linux Enterprise drivers may also be obtained from:

<ftp://download.nvidia.com/novell> or <http://www.nvidia.com>

#### Notes

The thermal solution used on this card is an active fan heatsink.

#### NVIDIA NVS 510 2GB Graphics

##### Form Factor

Low Profile, 2.713 inches × 6.3 inches, single slot

##### Graphics Controller

NVS 510 GPU  
Core Clock: 797 Mhz  
Memory Clock: 891 Mhz  
CUDA Cores: 192

##### Bus Type

PCI Express x16, Generation 2.0

##### Memory

2GB DDR3

##### Connectors

Four mini-DisplayPort.  
Four mini-DisplayPort to DisplayPort adapters included.  
(DisplayPort to DVI-D, DisplayPort to VGA, DisplayPort to HDMI, and DisplayPort to Dual-Link DVI adapters available as separate accessories)

##### Maximum Resolution

Mini-DisplayPort connectors support ultra-high-resolution panels (up to 3840 x 2160 @ 60Hz)

**NOTE:** This card supports up to four displays. For Windows XP, only 2 active displays are supported.

##### Image Quality Features

10-bit internal display processing, including hardware support for 10-bit scan-out

##### Display Output

DisplayPort with Multi-Stream Technology (MST) and High Bit Rate 2 (HBR2) support.

##### Digital Display Support

##### 1. DisplayPort Output

- Drives four DisplayPort enabled digital display at resolutions up to 3840 × 2160 at 60 Hz with reduced blanking, when connected natively using the 4 DisplayPort connectors on the NVS 510 graphics card.
- DisplayPort Multi-Stream Topology (MST) Technology: Supports various combinations of display resolutions and number of displays when using DisplayPort multi stream topology technology - up to a maximum of 4 monitors at a resolution of 1920 × 1200 at 60 Hz with reduced blanking.

##### 2. DVI-D Output

- Drives four digital displays at resolutions up to 1920 × 1200 at 60 Hz with

### Technical Specifications - Graphics

reduced blanking using DisplayPort to DVI-D single-link cable adaptors.  
- Drives four digital displays at resolutions up to 2560 × 1600 at 60 Hz with reduced blanking using DisplayPort to DVI-D dual-link cable adaptors.

#### 3. HDMI Output

- The NVS 510 graphics board is capable of driving four high definition (HD) panels up to resolutions of 1920 × 1080P at 60 Hz using DisplayPort to HDMI cable adaptors.

#### Analog Display Support

##### 1. VGA display output

- Drives four analog displays at resolutions up to 1920 × 1200 at 60 Hz using DisplayPort to VGA cable adaptors.

**Supported Graphics APIs** Full Microsoft DirectX 11, Shader Model 5.0 support  
Full OpenGL 4.3 support

**Available Graphics Drivers** Genuine Windows 7 Professional (64-bit and 32-bit)  
Microsoft Windows XP Professional (64-bit and 32-bit)  
Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation  
SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

**Power Consumption** 33.4 Watts

**Note** Heatsink cooler design is active.

#### Graphics Cable Adapters Notes

Graphics Cable Adapter option choice is available starting Feb 1 2013 for the following graphics cards:  
NVS 310, Quadro 410, Quadro K5000, FirePro V3900, FirePro W7000

New Graphics Cards introduced after Feb 1 2013 will be eligible for choosing Graphics Cable Adapters, unless otherwise specified.

No cable choice for NVS 300, NVS 510.

Maximum number of cables allowed is 8.

#### AMD FirePro V3900 1GB Graphics

**Form Factor** Full height, half length (full-height bracket included)

**Graphics Controller** AMD FirePro™ V3900 professional graphics

**Bus Type** PCI Express® x16, Generation 2.1

**Memory** 1GB DDR3 memory

**Maximum Resolution** 2560x1600 per display (5120x1600 max. horizontal resolution)

**Display Output** 1 DisplayPort® 1.2

1 Dual-link DVI

**Shading Architecture** Shader Model 5.0



### Technical Specifications - Graphics

<b>Supported Graphics APIs</b>	OpenCL™ 1.1, DirectX® 11 and OpenGL 4.2
<b>Available Graphics Drivers</b>	Genuine Windows® 7 Professional (64-bit and 32-bit) Genuine Windows Vista® Business (64-bit and 32-bit) Microsoft® Windows XP® Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)
	HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>
<b>Power Consumption</b>	<50W
<b>Note</b>	AMD Eyefinity technology can support multiple displays using a single enabled AMD FirePro™ professional graphics card; the number of supported displays varies by card model. Microsoft® Windows® 7, Windows Vista®, or Linux® is required in order to support more than 2 displays. Depending on the card model, native DisplayPort™ connectors and/or certified DisplayPort™ active or passive adapters to convert your monitor's native input to your card's DisplayPort™ or Mini-DisplayPort™ connector(s) may be required. See <a href="http://www.amd.com/firepro">www.amd.com/firepro</a> for details.

<b>NVIDIA Quadro 410 512MB Graphics</b>	<b>Form Factor</b>	Low Profile: 2.713 inches × 5.7 inches, single slot
	<b>Graphics Controller</b>	NVIDIA Quadro 410
	<b>Bus Type</b>	PCI Express x16, 3.0 compliant
	<b>Memory</b>	Size: 512MB DDR3
		Clock: 900MHz
		Memory Bandwidth: 14GB/s
	<b>Connectors</b>	One dual-link DVI-I connector One DisplayPort connector
	<b>Maximum Resolution</b>	Up to 2560 × 1600 (digital display) per display.
	<b>RAMDAC</b>	400 MHz integrated RAMDAC
	<b>Display Output</b>	Maximum resolution over DisplayPort: 2560 × 1600 × 32 bpp at 60 Hz (reduced blanking)
		Maximum resolution over DVI port: 2560 × 1600 × 32 bpp at 60 Hz (reduced blanking)
		Maximum resolution over VGA (through DVI to VGA cable): 2048 × 1536 × 32 bpp at 85 Hz
	<b>Shading Architecture</b>	Shader Model 5.0
	<b>Supported Graphics APIs</b>	DX11, OpenGL 4.2
	<b>Available Graphics Drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL)

### Technical Specifications - Graphics

SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or the latest HP qualified drivers are available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

SUSE Linux Enterprise drivers may also be obtained from:

<ftp://download.nvidia.com/novell> or <http://www.nvidia.com>

#### NVIDIA Quadro K600 1GB Form Factor Graphics

##### Graphics Controller

2.731" H x 6.3" L  
Single Slot, Low Profile  
Full Height Profile bracket installed  
Low Profile bracket included  
NVIDIA Quadro K600 Graphics Card  
Kepler GK107 GPU  
192 CUDA cores  
Max Power: 41 Watts

##### Bus Type

PCI Express 2.0 x16

##### Memory

1 GB GDDR3, 891 Mhz  
128-bit memory I/O path  
29 GB/s memory bandwidth

##### Connectors

1 DL-DVI(I) output, 1 DisplayPort output  
CTO: No video cable adapter included  
AMO: One DP-to-DVI adapter included with card

##### Maximum Resolution

Additional DVI-to-VGA, DisplayPort-to-VGA or DisplayPort-to-DVI adapters are available as accessories  
DisplayPort:  
- up to 3840 x 2160 x 30 bpp @ 60Hz  
- supports High Bit Rate 2 (HBR2) and Multi-Stream Transport (MST)

##### Image Quality Features

DL-DVI(I) output:  
- up to 2560 x 1600 x 32 bpp @ 60Hz  
10-bit internal display processing pipeline  
10-bit scan-out support

##### Display Output

VGA:  
- requires use of DVI-to-VGA and/or DP-to-VGA video cable adapters  
- 400 Mhz integrated RAMDAC  
- Max resolution: 2048 x 1536 x 32 bpp @ 85 Hz

DL-DVI(I):  
- Max resolution: 2560 x 1600 x 32 bpp @ 60 Hz

SL-DVI(I):  
- Max resolution: 1920 x 1200 x 32 bpp @ 60 Hz

DisplayPort:

### Technical Specifications - Graphics

	<ul style="list-style-type: none"><li>- Supports HBR2 and MST</li><li>- Max resolution: 3840 x 2160 x 30 bpp @ 60 Hz (only one monitor can be connected to the Quadro K600 DisplayPort connector at this resolution)</li><li>- Max number of daisy-chained monitors: 2</li></ul>
<b>Shading Architecture</b>	Full Microsoft DirectX 11 Shader Model 5.0
<b>Supported Graphics APIs</b>	OpenGL 4.3 DirectX 11 API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
<b>Available Graphics Drivers</b>	Windows 8 Pro 64-bit Windows 8 (China) 64-bit Genuine Windows 7 Professional (64-bit and 32-bit)  Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit) Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit)  HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>  SUSE Linux Enterprise drivers may also be obtained from: <a href="ftp://download.nvidia.com/novell">ftp://download.nvidia.com/novell</a> or <a href="http://www.nvidia.com">http://www.nvidia.com</a>
<b>Notes</b>	<ol style="list-style-type: none"><li>1. Quadro K600 offered as CTO does not include a video cable adapter. Video cable adapters must be ordered separately.</li><li>2. Quadro K600 offered as AMO includes one DP-to-DVI video cable adapter. Additional cables must be ordered separately.</li><li>3. Quadro K600 is Windows 8 Compliant.</li><li>4. A total maximum of 2 active monitors are supported across all display output types.</li></ol>

Technical Specifications - Multimedia and Audio Devices

HP Thin USB Powered Speakers	Frequency Response	F0 to 20kHz
	(-3dB, 24-bit/96kHz input)	
	Dimensions (H x W x D)	Speakers: 14.52 x 9.50 x 2.45 cm (5.72 x 3.74 x 0.96 in) per speaker

### Technical Specifications - Optical and Removable Storage

<b>HP DVD-ROM Drive</b>	<b>Description</b>	5.25-inch, half-height, tray-load
	<b>Mounting Orientation</b>	Either horizontal or vertical
	<b>Interface Type</b>	SATA/ATAPI
	<b>Dimensions (WxHxD)</b>	15.0 x 4.4 x 20.3 cm (5.9 x 1.7 x 8.0 in)
	<b>Disc Capacity</b>	<b>DVD-ROM</b> Single layer: Up to 4.7 GB Double layer: Up to 8.5 GB
	<b>Access Times</b>	<b>DVD-ROM Single Layer</b> < 140 ms (typical)
		<b>CD-ROM Mode 1</b> < 125 ms (typical)
		<b>Full Stroke DVD</b> < 250 ms (seek)
		<b>Full Stroke CD</b> < 210 ms (seek)
	<b>Power</b>	<b>Source</b> SATA DC power receptacle
		<b>DC Power Requirements</b> 5 VDC $\pm$ 5%-100 mV ripple p-p 12 VDC $\pm$ 5%-200 mV ripple p-p
		<b>DC Current</b> 5 VDC - <1000 mA typical, < 1600 mA maximum 12 VDC - < 600 mA typical, < 1400 mA maximum
<b>Operating Environmental</b> (all conditions non-condensing)	<b>Temperature</b>	41° to 122° F (5° to 50° C)
	<b>Relative Humidity</b>	10% to 90%
	<b>Maximum Wet Bulb Temperature</b>	86° F (30° C)
	<b>Operating Systems Supported</b>	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation, Removed reference to "Novell" because of acquisition and changed product reference to "SUSE Linux Enterprise Desktop 10 & 11", No driver is required for this device. Native support is provided by the operating system.

<b>HP DVD+/-RW Drive</b>	<b>Description</b>	5.25-inch, half-height, tray-load
	<b>Mounting Orientation</b>	Either horizontal or vertical
	<b>Interface Type</b>	SATA/ATAPI
	<b>Dimensions (WxHxD)</b>	15.0 x 4.4 x 20.3 cm (5.9 x 1.7 x 8.0 in)
	<b>Disc Formats</b>	DVD-RAM
		DVD+R DVD+RW DVD+R DL DVD-R DL DVD-R

### Technical Specifications - Optical and Removable Storage

	DVD-RW CD-R CD-RW	
<b>Disc Capacity</b>	<b>DVD-ROM</b>	8.5 GB DL or 4.7 GB standard
	<b>Full Stroke DVD</b>	< 250 ms (seek)
	<b>Full Stroke CD</b>	< 210 ms (seek)
<b>Maximum Data Transfer Rates</b>	<b>CD ROM Read</b>	CD-ROM, CD-R Up to 40X CD-RW Up to 32X
	<b>DVD ROM Read</b>	DVD-RAM Up to 12X DVD+RW Up to 8X DVD-RW Up to 8X DVD+R DL Up to 8X DVD-R DL Up to 8X DVD-ROM Up to 16X DVD-ROM DL Up to 8X DVD+R Up to 16X DVD-R Up to 16X
<b>Power</b>	<b>Source</b>	SATA DC power receptacle
	<b>DC Power Requirements</b>	5 VDC $\pm$ 5%-100 mV ripple p-p 12 VDC $\pm$ 5%-200 mV ripple p-p
	<b>DC Current</b>	5 VDC -1000 mA typical, 1600 mA maximum 12 VDC -600 mA typical, 1400 mA maximum
<b>Operating Environmental</b> (all conditions non-condensing)	<b>Temperature</b>	41° to 122° F (5° to 50° C)
	<b>Relative Humidity</b>	10% to 90%
	<b>Maximum Wet Bulb Temperature</b>	86° F (30° C)
	<b>Operating Systems Supported</b>	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation SUSE Linux Enterprise Desktop 10 & 11
	<b>Kit Contents</b>	No driver is required for this device. Native support is provided by the operating system. HP SATA SuperMulti DVD Writer Drive, Roxio Easy Media Creator software, Intervideo WinDVD Software, installation guide, and DVD+R media.

<b>HP Blu-Ray Writer</b>	<b>Description</b>	5.25-inch, half-height, tray-load
	<b>Mounting Orientation</b>	Either horizontal or vertical

### Technical Specifications - Optical and Removable Storage

<b>Interface Type</b>	SATA		
<b>Dimensions (WxHxD)</b>	15.0 x 4.4 x 20.3 cm (5.9 x 1.7 x 8.0 in)		
<b>Disc Formats</b>	BD-ROM BD-R BD-RE DVD-RAM DVD+R DVD+RW DVD+R DL DVD-R DL DVD-R DVD-RW CD-R CD-RW		
<b>Disc Capacity</b>	<b>DVD-ROM</b>	8.5 GB DL or 4.7 GB standard	
	<b>Blu-ray</b>	50 GB DL or 25 GB standard	
	<b>Full Stroke DVD</b>	< 250 ms (seek)	
	<b>Full Stroke CD</b>	< 210 ms (seek)	
	<b>Blu-ray</b>	Blu-ray	
	<b>Startup Time</b> (Time to drive ready from tray loading)	BD-ROM (SL/DL)	25S / 28S
		BD-R (SL/DL)	25S / 28S
		BD-RE (SL/DL)	25S / 28S
		DVD-ROM (SL/DL)	18S / 18S
		DVD-R (SL/DL)	25S / 25S
		DVD-RW	25S
		DVD+R (SL/DL)	25S / 25S
		DVD+RW	25S
		DVD-RAM	45S
		CD-ROM	45S
<b>Maximum Data Transfer Rates</b>	<b>CD ROM Read</b>	CD-ROM	Up to 40X
		CD-R	Up to 40X
		CD-RW	Up to 40X
	<b>DVD ROM Read</b>	DVD-RAM	Up to 5X
		DVD+RW	Up to 10X
		DVD-RW	Up to 10X
		DVD+R DL	Up to 8X
		DVD-R DL	Up to 8X
		DVD-ROM	Up to 16X
		DVD-ROM DL	Up to 8X
		DVD+R	Up to 12X
		DVD-R	Up to 12X
		BD-ROM	Up to 6X
	<b>Blu-Ray</b>	BD-ROM	Up to 6X

### Technical Specifications - Optical and Removable Storage

		BD-ROM DL	Up to 4.8X
		BD-R	Up to 6X
		BD-R DL	Up to 4.8X
		BD-R	Up to 6X
		BD-RE SL/DL	Up to 4.8X
Power	Source	SATA DC power receptacle	
	DC Power Requirements	5 VDC ± 5%-100 mV ripple p-p 12 VDC ± 10%-100 mV ripple p-p	
	DC Current	5 VDC -900 mA typical, 1200 mA maximum 12 VDC -1000 mA typical, 1600 mA maximum	
Operating Environmental (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)	
	Relative Humidity	15% to 80%	
	Maximum Wet Bulb Temperature	86° F (30° C)	
	Operating Systems Supported	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation, SUSE Linux Enterprise Desktop 10 & 11	
		<p>* No driver is required for this device. Native support is provided by the operating system.</p> <p>** RHEL WS4 not supported on Z200/Z200SFF</p>	
	Kit Contents	HP Blue Laser RW Drive, Roxio Easy Media Creator software, Intervideo WinDVD Software, installation guide.	
	Disclaimer	As Blu-Ray is a new format containing new technologies, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-Ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD-DVD movies cannot be played on this workstation.	
HP 14-in-1 Media Card Reader	Description	Supports hardware ECC (Error Correction Code) function Supports hardware CRC (Cyclic Redundancy Check) function Supports MS 4-bit parallel transfer mode Supports MS-PRO 4-bit parallel transfer mode Supports MS PRO-HG Duo 4-bit parallel transfer mode Supports SD 4-bit parallel transfer mode Supports UHS-104 SD 4-bit card (version 3.0) Supports CF v6.0 with PIO mode 6 and Ultra DMA 7 mode	
	Interface Type	USB 3.0 High-speed interface	



### Technical Specifications - Optical and Removable Storage

	Note: If there is a USB2 connection, USB2 transfer speeds are supported.
<b>Dimensions (WxHxD)</b>	4.9 x 4 x 1 in (124.5 x 101.6 x 25.4 mm)
<b>Supported Media Types</b>	CompactFlash Type I CompactFlash Type II Microdrive Secure Digital Card (SD) Secure Digital High Capacity (SDHC) SD Extended Capacity Memory Card (SDXC) Memory Stick Memory Stick Select Memory Stick Duo (MS Duo) Memory Stick PRO (MS PRO) Memory Stick PRO Duo (MS PRO Duo) Memory Stick PRO-HG Duo MagicGate Memory Stick (MG) MagicGate Memory Stick Duo Note: These additional media types are supported with a card adapter. Memory Stick Micro (M2) miniSD miniSD High Capacity Micro SD Memory Card (MicroSD) Micro SD High Capacity Memory Card (MicroSDHC)
<b>Operating Environmental (all conditions non-condensing)</b>	10°C 10% R.H. ≥ 24 hours 10°C 90% R.H. ≥ 24 hours 20°C 90% R.H. ≥ 24 hours 30°C 90% R.H. ≥ 24 hours 40°C 90% R.H. ≥ 24 hours 50°C 90% R.H. ≥ 24 hours 50°C 10% R.H. ≥ 24 hours  Extremes: 140°F (60°C) @ 80% R.H. for 96 hours -22°F (-30°C) @ 20% R.H. for 48 hours No power applied Delta °C < 1.0°C/min Delta % R.H. < 1.5% R.H./min Note: Test Parameters/Conditions - Power applied, unit operating on system ±5%
<b>Operating Systems Supported</b>	Windows 8 Pro (64-bit)* Windows 8 (64-bit)* Windows 7 Ultimate (32-bit)** Windows 7 Ultimate (64-bit)** Windows 7 Professional (32-bit)** Windows 7 Professional (64-bit)** Windows 7 Home Basic** Windows 7 Home Premium (32-bit)** Windows 7 Home Premium (64-bit)** Windows Vista Business 64

### Technical Specifications - Optical and Removable Storage

Windows Vista Business 32

Windows Vista Home Basic 32

Windows XP Professional

Windows XP Home 32

No driver is required for this device. Native support is provided by the operating system.

Note: Not all features are available in all editions of Windows 8. Systems may require upgraded and/or separately purchased hardware, drivers and/or software to take full advantage of Windows 8 functionality. See <http://www.microsoft.com>.

Note: Not all features are available in all editions of Windows 7. This system may require upgraded and/or separately purchased hardware to take full advantage of Windows 7 functionality. See <http://www.microsoft.com/windows/windows-7/> for details.

#### Kit Contents

Media card reader, 5.25" bracket/rails/bezel, Install Guide, IO & Security Software and Documentation CD

#### Approvals

USB-IF, WHQL, Compliant with USB Mass Storage Class Bulk only

### Technical Specifications - Controller Cards

<b>HP IEEE 1394b FireWire PCIe Card</b>	<b>Data Transfer Rate</b>	Supports up to 800 Mbps
	<b>Devices Supported</b>	IEEE-1394 compliant devices
	<b>Bus Type</b>	PCIe card full height PCIe slots
	<b>Ports</b>	Two IEEE-1394b bilingual 9-Pin Connector (Rear)
	<b>Internal Connectors</b>	One 10-Pin header Custom Connector
	<b>System Requirements</b>	Windows 7 Professional 32-bit and 64-bit, Microsoft® Windows® XP Professional, Windows XP Home, Windows Vista, SLED 11 and RHEL 6. Intel Pentium® G series or higher processor, 128-MB RAM, 1-GB Hard Drive, CD-ROM drive, built in sound system, Available PCIe slot.
	<b>Temperature – Operating</b>	50° to 131° F (10° to 55° C)
	<b>Temperature – Storage</b>	–22° to 140° F (–30° to 60° C)
	<b>Relative Humidity – Operating</b>	20% to 80%
	<b>Compliances</b>	FCC Part 15B, cULus 60950, CE Mark EN55022B(1995)/EN55024-1998 STD, Taiwan BSMI CNS13438, Korea MIC
	<b>Operating Systems Supported</b>	Windows 7 Professional 32-bit and 64-bit, Windows Vista® Business 32-bit and 64-bit, Windows® XP Professional, XP Professional 64-bit, RHEL 6 and SLED 11.
<b>HP Thunderbolt-2 PCIe 1-port I/O Card</b>	<b>Data Transfer Rate</b>	Supports up to 20 Gb/s (20,000 Mb/s)
	<b>Devices Supported</b>	Thunderbolt™ certified devices
	<b>Bus Type</b>	PCIe card, full or half height PCIe slots
	<b>Ports</b>	One Thunderbolt™ 2 external 20-Pin output connectors (Rear)
	<b>Internal Connectors</b>	One 5-Pin header connector
	<b>System Requirements</b>	Genuine Windows 7 Professional 64-bit, Genuine Windows 8.1 64-bit, Intel i5 series or higher processor, 128-MB RAM, 1-GB Hard Drive, available PCIe slot.
	<b>Temperature - Operating</b>	50° to 131° F (10° to 55° C)
	<b>Temperature - Storage</b>	–22° to 140° F (–30° to 60° C)
	<b>Relative Humidity - Operating</b>	20% to 80%
	<b>Compliances</b>	FCC Part 15B, cULus 60950, CE Mark EN55022B(1995)/EN55024-1998 STD, Taiwan BSMI CNS13438, Korea MIC
	<b>Operating Systems Supported</b>	Genuine Windows 7 Professional 64-bit, Genuine Windows 8.1 64-bit.
	<b>Kit Contents</b>	HP Thunderbolt™ 2 PCIe 1-port I/O Card, full height and half height bracket, DisplayPort to DisplayPort cable, internal header cables(2), user documentation and warranty card.
	<b>Warranty</b>	The HP Thunderbolt™ 2 PCIe 1-port I/O Card has a one-year Limited Warranty or the remainder of the warranty of the HP supported product in which it is installed. Technical support is available seven days a week, 24 hours a day, by phone, as well as online support forums. Certain restrictions and exclusions apply.

## Technical Specifications - Networking and Communications

© 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Intel, Xeon are trademarks of Intel Corporation in the U.S. and other countries. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation. Windows 7 and Windows Vista is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries.

Technical Specifications - Networking and Communications

Date of change:	Version History:		Description of change:
June 1	v16 to June 1	Changed	
		Added	IdNumber
		Removed	